

Abiko A 2504 FLF Fully-Insulated Flat Receptacle, 4.8 × 0.8 mm

Brand: Abiko Part No: A 2504 FLF HS: 8536.90
Insulated Flat Receptacles

Description

Abiko A 2504 FLF — fully-insulated flat receptacle (female push-on) for a 4.8 × 0.8 mm flat push-on connection. The tin-plated brass contact carries a tin-plated copper crimp barrel and a full-body halogen-free Nylon (PA) insulation sleeve. Operating temperature -20 °C to +105 °C; insulation UL-approved. Crimped to stranded or flexible copper conductors (IEC 60228) with matching Abiko/Elpress dies. Applied in control panels, switchboards, appliance wiring and marine installations. Manufacturer: Abiko (Elpress Group). Manufacturer part number: A 2504 FLF. EAN: 7070920011458.

Specifications

Type	Fully-Insulated flat receptacle (female push-on) per DIN 46247
Tab dimension	4.8 × 0.8 mm
Material	Brass contact body, tin-plated; copper crimp barrel, tin-plated
Insulation	Nylon (PA), halogen-free, easy-entry (sleeve covers full body)
Conductor	Stranded / flexible copper (IEC 60228)
Operating temperature	-20 °C to +105 °C
Approvals	Insulation UL-approved
Standard	DIN 46247
Series	Abiko A (pre-insulated)
Manufacturer part number (MPN)	A 2504 FLF
EAN / GTIN	7070920011458
HS code	8536.90

