ASCO 8210 Solenoid Valves — Series Guide and Cross-Reference

cBallast Technical Sourcing · General service solenoid valves · issued 2026-11-09 · cballast.com/documents/asco-8210-solenoid-valve-series-cross-reference

The ASCO Series 8210 general-service solenoid valve family explained — what the 8210G numbering carries, pilot-operated against direct-acting behaviour and the minimum pressure differential that follows, NC and NO functions, coil and connection options, media and seal pairing — plus the honest cross-reference landscape toward Danfoss EV220, Burkert and Parker general-service lines, and the selection table that prevents the classic zero-differential mistake.

The short version

Series 8210 is ASCO's general-service 2-way workhorse — brass (and stainless variants) bodies, NPT connections from 3/8 to 2-1/2 in., for water, air, light oils and inert gases. The family identity (8210) plus the catalogue suffix fixes body size, orifice, function and construction; the famous 8210G002 is the 1/2 in. NPT normally-closed brass unit found on wash-down skids, air headers and water lines on five continents. The G marks the current-generation construction with the encapsulated Red-Hat class coil system.

Most of the family is pilot-operated — and that is the trap. A pilot-operated diaphragm valve uses line pressure to open fully: it needs a minimum pressure differential (the 8210 class figures sit around 0.3–0.7 bar by model) to lift and to stay open. On gravity lines, suction lines, recirculation loops and tank balance lines that differential does not exist, the valve "chatters" or never opens, and the diagnosis is in the datasheet line nobody read. Zero-differential duties take direct-acting or coupled-diaphragm designs.

Function letters first: NC (closed without power — the fail-safe default for most process and safety duties) or NO (open without power — cooling and fire-water-adjacent duties). Energise-to-open NC on a safety interlock, never NO-because-it-was-on-the-shelf.

Seals pair to media: NBR for water, air, light oils; EPDM for hot water and steam-adjacent duties (never oils); FKM for fuels and hydrocarbons; PTFE in steam designs. Wrong elastomer is the second-most-common field failure after the differential trap.

Coils are the consumable: standardised encapsulated coils in 12/24 V DC and 24/110-120/220-240 V AC, DIN or junction-box connections, continuously rated — a dead coil is a spare-part event, and voltage/frequency must match exactly (an AC coil on DC, or 60 Hz coil at 50 Hz, runs hot and dies young).

1. Reading the family: what the number carries

Element | Example | Meaning |

Series | 8210 | 2-way general service, diaphragm/piston pilot-operated family (8262/8263 are the small direct-acting siblings; 8320 the 3-way family) |

Construction letter | G | Current-generation construction and coil system |

Catalogue number | 002, 003, 004, 054, 087 ... | Fixes pipe size, orifice, function (NC/NO), body and seal build — read from the catalogue table, they are not sequential logic |

Voltage suffix | e.g. 24/DC, 120/60 | Coil voltage and frequency, stated at order |

Worked example — 8210G002: 2-way NC, brass body, 1/2 in. NPT, NBR seat class, pilot-operated diaphragm, the general-service default for water and air at line pressures within its published differential window. The catalogue row for each number states: pipe size, orifice (mm/in.), Cv/Kv flow factor, minimum and maximum operating pressure differential by medium (air, water, light oil) and by coil power, temperature limits, and the approvals carried. That row — not the series headline — is the specification.

2. Pilot-operated vs direct-acting: the decision that matters

Design | How it opens | Min. differential | Consequence |

Direct-acting | Solenoid lifts the seat directly | 0 bar | Works at zero differential; small orifices only (coil force is the limit) — the 8262/8263 class and small Danfoss EV210 class |

Pilot-operated diaphragm | Solenoid opens a pilot; line pressure lifts the diaphragm | ≈ 0.3–0.7 bar typical | Big orifices and flows from small coils; must have the differential across it, always |

Coupled / assisted-lift diaphragm | Solenoid mechanically assists the diaphragm | 0 bar | The zero-differential answer at larger sizes (Danfoss EV220B's coupled variants and ASCO's assisted designs) |

The field symptom table writes itself: a pilot-operated valve on a gravity drain hums and passes nothing (no differential to lift); one on a line with downstream back-pressure equal to upstream never closes cleanly; one sized "big to be safe" on a trickle flow chatters its diaphragm to death. Match design to differential first, then size by Kv for the real flow — oversizing a solenoid valve is not generosity, it is premature diaphragm failure.

3. Media, seals and temperature

Medium | Seal | Notes |

Water, air, inert gas | NBR | The default build; watch water hammer on fast-closing valves — add arrestors or slow-closing designs on long runs |

Hot water, glycols | EPDM | Never oils or fuels on EPDM |

Fuels, oils, hydrocarbons | FKM | The fuel-skid build; check aromatic content vs the compound |

Steam | PTFE designs | Dedicated steam constructions with their own series/numbers — not a seal swap |

Refrigerants | — | A different product family entirely: Danfoss EVR class per our solenoid valve finder |

Seawater, aggressive media | Stainless/bronze bodies, FKM/EPDM by medium | Brass dezincifies in seawater; body material is part of the media decision |

4. Cross-reference landscape, honestly drawn

Duty | ASCO | Peer-class equivalents | Cross caveat |

General service 2-way, 3/8–2 in., water/air/oil | 8210G family | Danfoss EV220B, Burkert 6213/5281 class, Parker 7321 class | Match function (NC/NO), orifice/Kv, min. differential, seal, body, coil voltage and connection — six attributes, every time |

Small direct-acting | 8262/8263 | Danfoss EV210B, Burkert 6013 class | Orifice and power; DC performance differs between makers |

3-way pilot/vent duties | 8320 | Peer 3-way families | Porting logic (U, E, D functions) must match the circuit |

NAMUR actuator pilots | — | ASCO SCG531 NAMUR 3/2–5/2 and 5/2 spool class | NAMUR interface standardises mounting; spool function and pilot pressure still match by data — see the pneumatic valve finder |

A cross is complete when the six attributes line up and the approvals follow (UL/CSA on the American side, the EU pressure and potable-water schemes on the European, Ex-certified coil systems where zoned — marking logic in the ATEX/IECEx guide). The reflex "EV220B equals 8210" is right often enough to be dangerous: the differential windows and seal builds differ by catalogue row, which is why we cross by row, not by family.

5. Installation and the three classic field failures

Install: flow arrow with the flow, coil upright where practical, strainer upstream on dirty media (a Y-strainer costs less than one diaphragm), and unions either side for service. Failure one — won't open: pilot-operated valve at zero differential (see section 2), or a dead coil: check voltage at the coil, then coil resistance; coils are stocked spares. Failure two — won't close / weeps: debris on the seat or a pinholed diaphragm — rebuild kits (diaphragm, springs, core assembly) restore the valve for a fraction of replacement, by valve catalogue number. Failure three — burnt coils repeating: wrong voltage/frequency, a jammed core (scale, debris) making the AC coil draw locked-rotor current forever, or water in the junction box. The reorder key for all of it is the nameplate: series + catalogue number + voltage. Photograph it before the plate corrodes — the same advice as every order-number decoder we publish.

How buying works at cballast. We quote ASCO, Danfoss, Burkert and peer solenoid valves by nameplate code or by the six-attribute set, with coils and rebuild kits itemised and crosses confirmed per catalogue row. Accounts are vetted at onboarding; first order prepaid; established accounts on credit terms with repeat discounts; public bodies and utilities invoiced against purchase order from the first order. RFQs to sales@cballast.com.

Frequently asked questions

What is an ASCO 8210G002?The 1/2 in. NPT, 2-way normally-closed, brass-body, pilot-operated general-service solenoid valve in ASCO's Series 8210 — the default water/air shutoff valve of countless skids. Its catalogue row fixes orifice, Kv, differential window, seals and temperature; order it with the coil voltage stated.
Why won't my solenoid valve open on a gravity line?Because it is pilot-operated and needs a minimum pressure differential (typically 0.3–0.7 bar on the 8210 class) to lift its diaphragm. Gravity drains, suction and balance lines need a direct-acting or coupled/assisted-lift (zero-differential) design — that is a different catalogue number, not a bigger coil.
Is the Danfoss EV220B equivalent to the ASCO 8210?Family-to-family, yes — both are pilot-operated general-service 2-way lines. Row-to-row, only when function, size/orifice, minimum differential, seal compound, body material and coil match; the EV220B also offers coupled (zero-differential) variants the plain 8210 rows do not. We cross by catalogue row with the datasheets open.
NC or NO — which do I choose?By the safe state on power failure: NC (closed de-energised) for most process, fuel and safety duties — energy opens, failure closes; NO (open de-energised) where loss of power must keep flow (cooling, some fire duties). The letter is part of the catalogue number, not a site setting.
Can I rebuild a solenoid valve instead of replacing it?Usually: rebuild kits (diaphragm/core/springs/seals) exist per catalogue number and cure seat leakage and weeping for a fraction of a new valve — provided the body is sound and the medium matched the seals in the first place. Burnt coils are separate spares; repeated coil deaths mean a jammed core or wrong voltage, not bad luck.
Who supplies ASCO 8210 valves, coils and rebuild kits?cballast.com quotes the 8210 family and its peers by nameplate code, with coils in every standard voltage and rebuild kits per row, plus confirmed equivalents where lead time or preference demands. Send the nameplate photo to sales@cballast.com.

References and related guides

Sources referenced: ASCO (Emerson) Series 8210/8262/8320 catalogue tables (sizes, orifices, Kv/Cv, differential windows, coils); Danfoss EV210B/EV220B documentation; Burkert general-service valve data; EN 161/approval schemes where applicable; standard solenoid-valve installation practice.

Solenoid valve finder — Danfoss EV210/EV220/EV250

Pneumatic directional valve finder

Pipeline strainers — Y and basket selection

Water regulating valves — Penn V46

Danfoss AVTA thermostatic water valves

Questions on a catalogue row, a coil or a cross: write to sales@cballast.com. We answer whether or not you buy from us.

Part numbers and designations are those of the original manufacturers and are given for identification. cBallast is an independent supplier. © cBallast 2026 · cballast.com