

Pipe Thread Chart — BSP (G/R), NPT and Metric: Dimensions, TPI and Identification

cBallast Technical Sourcing · Pipe threads and fittings · issued 2026-10-04 · cballast.com/documents/bsp-npt-metric-thread-chart

Dimension table for BSPP (G), BSPT (R), NPT and metric fine threads used on fittings, glands and sensors: major diameter, threads per inch or pitch, tap drill, how to tell them apart with calipers, and which pairs seal together.

The three families

BSPP / G (ISO 228-1) is a parallel British pipe thread that seals on a gasket, O-ring or bonded washer under the fitting shoulder — never in the thread itself. BSPT / R (ISO 7-1) is the tapered version that seals in the thread with sealant or PTFE tape; Rc is the tapered female, Rp the parallel female that mates with R male. NPT (ASME B1.20.1) is the American tapered thread with a 60° flank angle against the 55° of the British forms — the two taper families are not interchangeable even where diameters look close. Metric fine threads (M12 × 1.5, M20 × 1.5 ...) are parallel and dominate cable glands and sensor bosses.

Dimension table

Nominal | G/R major Ø (mm) | BSP TPI | NPT major Ø (mm) | NPT TPI | G tap drill (mm) |

1/8" | 9.73 | 28 | 10.24 | 27 | 8.8 |

1/4" | 13.16 | 19 | 13.62 | 18 | 11.8 |

3/8" | 16.66 | 19 | 17.05 | 18 | 15.25 |

1/2" | 20.96 | 14 | 21.22 | 14 | 19.0 |

3/4" | 26.44 | 14 | 26.57 | 14 | 24.5 |

1" | 33.25 | 11 | 33.23 | 11.5 | 30.75 |

1 1/4" | 41.91 | 11 | 41.98 | 11.5 | 39.5 |

1 1/2" | 47.80 | 11 | 48.05 | 11.5 | 45.25 |

2" | 59.61 | 11 | 60.09 | 11.5 | 57.0 |

Note the classic trap at 1/2" and 3/4": G and NPT major diameters differ by well under a millimetre but the flank angles differ (55° vs 60°), so a forced assembly leaks under vibration. At 1" the TPI differ (11 vs 11.5) — a thread gauge settles it instantly.

Identification in four steps

Parallel or tapered? Lay a straight edge on the crests — a taper is visible over 3–4 threads.

Measure the major diameter with calipers on a male thread and find the closest row above; pipe threads are named for the bore of the original steel pipe, not the thread OD.

Count TPI with a pitch gauge: 19 or 14 says British; 18 says NPT; a metric pitch (1.5 mm) says gland thread.

Check the seat. A flat face, O-ring groove or 30° cone means the joint seals on the face and the thread is parallel G; bare tapered threads mean R or NPT with sealant.

Catalogue examples: JIC-to-NPT adapters, M20 × 1.5 Ex e cable glands and 1/2" NPT gauge valves. Flange-face dimensions live in the PN16 flange chart; refrigeration flare threads (7/16"-20 UNF ...) are covered in the SAE flare guide.

Frequently asked questions

What diameter is a 1/2 inch BSP thread? A 1/2" BSP (G 1/2) male thread measures 20.96 mm across the crests with 14 threads per inch. Are BSP and NPT threads interchangeable? No. BSP uses a 55° flank angle and NPT 60°, and the TPI differs at several sizes; a mixed joint may screw together but will not seal reliably. How does a G (BSPP) thread seal? On the face: a bonded washer, gasket or O-ring under the fitting shoulder carries the seal, while the parallel thread only provides clamping. What thread is on a standard cable gland? European glands use metric fine threads — most commonly M16 × 1.5, M20 × 1.5, M25 × 1.5 — parallel, sealed by a washer or O-ring at the entry face. How do I tell NPT from BSPT quickly? Count threads per inch: 18 TPI at 1/4"–3/8" or 11.5 TPI at 1" and above means NPT; 19 or 11 TPI means the British taper. Both are tapered, so only the pitch and flank angle separate them.

Part numbers and designations are those of the original manufacturers and are given for identification. cBallast is an independent supplier. © cBallast 2026 · cballast.com