

JIS B2220 10K Flange Dimensions — DN15 to DN300 (Bolt Circles, Bolting, Thickness)

cBallast Technical Sourcing · Pipe flanges · issued 2026-10-04 · cballast.com/documents/jis-b2220-10k-flange-dimensions

Dimension table for JIS B2220 10K slip-on/plate flanges from 15A to 300A: outside diameter, bolt-circle diameter, number and size of bolts, flange thickness, with guidance on mating JIS to EN/PN and ASME class flanges.

JIS 10K dimension table

Nominal (A/DN) | OD (mm) | PCD (mm) | Bolts | Bolt size | Thickness (mm) |

15A | 95 | 70 | 4 | M12 | 12 |

20A | 100 | 75 | 4 | M12 | 14 |

25A | 125 | 90 | 4 | M16 | 14 |

32A | 135 | 100 | 4 | M16 | 16 |

40A | 140 | 105 | 4 | M16 | 16 |

50A | 155 | 120 | 4 | M16 | 16 |

65A | 175 | 140 | 4 | M16 | 18 |

80A | 185 | 150 | 8 | M16 | 18 |

100A | 210 | 175 | 8 | M16 | 18 |

125A | 250 | 210 | 8 | M20 | 20 |

150A | 280 | 240 | 8 | M20 | 22 |

200A | 330 | 290 | 12 | M20 | 22 |

250A | 400 | 355 | 12 | M22 | 24 |

300A | 445 | 400 | 16 | M22 | 24 |

Values for the common JIS B2220 10K slip-on and plate flange pattern with raised face; hub and weld-neck variants share OD, PCD and bolting. Japanese drawings quote nominal bore with the suffix A (50A = DN50 = 2").

JIS against PN and ASME

JIS 10K, EN 1092-1 PN10/PN16 and ASME class 150 flanges do not interchange: at DN50, JIS 10K drills 4 × M16 on a 120 mm circle, PN16 drills 4 × 18 mm holes on 125 mm (PN16 chart), and class 150 drills 4 × 3/4" holes on 120.6 mm — close enough to tempt, far enough to leak or crack. The only safe mixed joint is a purpose-made adapter spool. Japanese-built vessels carry JIS piping throughout, so spares for them (gaskets, bolting, M16 bolts, counter-flanges) must be ordered to JIS tables; European yards follow EN 1092-1 (PN10/PN25) and US-spec plants ASME B16.5 (B16.47 large diameters).

Higher JIS ratings

The same B2220 system defines 5K (lighter, often found on non-critical shipboard lines), 16K and 20K patterns with their own PCDs and bolting — a 10K gasket or counter-flange does not fit a 16K line of the same bore. The rating is cast or stamped on the flange rim together with the nominal size; when it is unreadable, identify by measuring OD, PCD and bolt count against the tables before ordering mating parts.

Frequently asked questions

What are the dimensions of a JIS 10K 50A flange? A JIS B2220 10K 50A (DN50) flange is 155 mm outside diameter with four M16 bolts on a 120 mm bolt circle, 16 mm thick. Are JIS 10K and PN16 flanges interchangeable? No — at most sizes the bolt-circle diameters and hole counts differ (DN50: 120 mm/4 holes vs 125 mm/4 holes), so they neither bolt up correctly nor seal reliably. What does 50A mean on a Japanese drawing? The nominal bore in millimetres with the JIS suffix A: 50A equals DN50 (2 inch nominal). Does JIS 10K match ASME class 150? No. Dimensions are close at some sizes but hole diameters, PCDs and facing differ; use a transition spool where the two systems meet. Which JIS rating is on my flange? JIS flanges are marked with size and rating (5K/10K/16K/20K) on the rim; if unreadable, measure OD, bolt-circle diameter and bolt count and match them to the B2220 tables.

Part numbers and designations are those of the original manufacturers and are given for identification. cBallast is an independent supplier. © cBallast 2026 · cballast.com