Sourcing Industrial & Marine Valves — Supplier Guide

cBallast Technical Sourcing · Valve procurement · issued 2026-11-09 · cballast.com/documents/sourcing-industrial-marine-valves-supplier-guide

The practical answer to "who should we contact to get valves": the three sourcing channels (manufacturer, stocking distributor, project trader) and when each wins, the qualification table — certifications, approvals, material certificates, fire-safe and class paperwork — that separates a supplier from a reseller, the RFQ anatomy that gets comparable quotes on the first pass, lead-time and stock reality by valve family, OEM against equivalent thinking on classed and critical service, and the red flags that predict a bad delivery before the order is placed.

The short version

Who to contact depends on what the valve is: commodity line valves (ball, gate, globe, check, butterfly in standard materials) are a stocking-distributor buy — speed and consolidation win; engineered and classed valves (control valves, safety valves with set pressures, sea valves under survey, exotic alloys) need the manufacturer or its authorised channel in the loop for sizing, certificates and serial-bound paperwork; project and refit packages want one supplier consolidating both layers against the schedule — the model we run at cballast.

Qualification is paperwork plus honesty, not logo count: the table below — quality system, pressure directive compliance, the approvals the duty demands (class type approval for shipboard systems, fire-safe test evidence where specified, drinking-water approvals on potable lines), EN 10204 3.1 material certificates as the working default on pressure service — plus the behavioural tests: does the supplier state what it does not know, flag substitutions explicitly, and put lead times in writing?

The RFQ decides the quote quality. A valve line that states type, size and rating, standard, end connections and face (facing guide), body/trim materials, operation, media and temperature, approvals and certificate level gets three comparable offers; "DN80 valve, 10 bar, ASAP" gets three guesses.

Lead-time truth by family: standard commodity sizes are stock-to-weeks; actuated packages and engineered valves run weeks-to-months; exotic materials and class-witnessed items are long-lead and belong in the survey planning cycle, not the emergency basket.

Replacement reality on ships and old plants: the flange tells the story — identify the drilling first (PN16, Class 150, JIS 10K, or a legacy table pattern) and the right valve follows; guessing the standard is how a "correct DN100 valve" arrives undrillable.

1. The three channels — and when each is the right call

Channel | Wins when | Loses when |

Manufacturer / authorised network | Engineered valves (control, safety with set pressure, cryogenic, exotic alloys); warranty-period equipment; serial-bound spares and actuation retrofits | Commodity lines — minimums, lead times and freight beat the unit price advantage |

Stocking distributor | Commodity and semi-engineered valves across brands; mixed-line consolidation; speed; one accountable counterparty for an RFQ of forty lines | One-off exotic engineering a stock book cannot answer — the good ones say so and bring the maker in |

Project trader / buying agent | Large newbuild packages priced across markets | Aftermarket and operations: no stock, no documentation depth, no accountability when the ship needs the valve on Thursday |

The honest structural answer to "who should my company contact": for operations and maintenance, qualify one or two stocking suppliers who carry the commodity layer and demonstrably know when to escalate to manufacturers — then let them run both layers on one paper trail. The qualification table is how you test that claim before the first order, and the MRO distribution primer explains the economics underneath it.

2. Supplier qualification — the table to score against

Criterion | What to ask for | Pass looks like |

Quality system | ISO 9001 class certification, and who actually holds it | Current certificate in the supplier's own name, not a forwarded factory PDF |

Pressure equipment compliance | PED 2014/68/EU position for the categories quoted (CE where applicable) | Correct category talk, not "CE on request" |

Material certification | EN 10204 3.1 per line on pressure parts; 3.2 path where class witnesses | Certs delivered with goods, heat numbers matching — sample one line and check |

Approvals for the duty | Class type approval for shipboard systems; fire-safe test evidence (API 607/ISO 10497 class) where specified; drinking-water approvals on potable lines | The certificate for the actual valve series quoted, not a brand-level brochure |

Traceability & substitution discipline | How substitutions are flagged; marking vs certs | Equivalents stated per line with basis — never silent brand swaps |

Stock and lead-time honesty | Stock proof on claimed lines; written lead times with tolerances | A supplier who says "6–8 weeks" in writing beats one who says "fast" on the phone |

Technical escalation | What happens when the inquiry exceeds the stock book | Named manufacturer relationships; sizing questions answered or escalated, not improvised |

Commercial hygiene | Quote validity, Incoterms, payment terms, export paperwork (HS lines) | Boring, complete paperwork — the leading indicator of boring, complete deliveries |

3. RFQ anatomy — the line that gets three comparable quotes

Element | Example | Omitting it costs |

Type and pattern | Ball valve, full bore, floating; globe, straight; butterfly, wafer/lugged | Pattern mismatches at installation |

Size and rating | DN80 PN16; 3" Class 150; JIS 10K | The undrillable-flange delivery |

Standard and face | EN 1092-1 RF; flanged per JIS B2220; grooved per groove spec; threaded BSPP | Gasket and bolting chaos |

Materials, body/trim/seals | GGG40/316 trim/EPDM; full 316; bronze for seawater | Corrosion surprises; elastomer-media failures |

Operation | Lever, gear, bare stem per ISO 5211, actuated (state air/electric, fail position) | Actuation retrofits that cost more than the valve |

Media, temperature, pressure | Seawater 0–40 °C; steam 10 bar; thermal oil 200 °C | Wrong seats and the pT lessons of the gasket world |

Approvals and certificates | Class TA, fire-safe, 3.1 certs per line | Survey rejections after installation |

Quantity, need-by, delivery point | 4 pcs, CW46, yard gate / last port | Air freight that planning would have sailed |

For the recurring families, our model-code and cross-reference guides make the specification half of this automatic: ASCO 8210 solenoids, Parker D1VW hydraulic directionals, and the general valve programme quoted against the flange finder's standards logic.

4. OEM, equivalent, and the classed-service line

Three honest tiers. OEM-mandatory: warranty-period equipment, serial-bound control and safety valves (set-pressure items travel with their certificates), and anything the class survey record names by maker — substitute here and the paperwork fails even when the metal fits. Equivalent-legitimate: commodity isolation and check valves where standard, rating, materials and approvals all match — the equivalence basis stated on the quote line, the same discipline we apply to fuses and seals. Engineering-judgement: everything between — sea valves on survey, fire-main butterflies, bellows-sealed chemistry — where the question is not "does a cheaper valve exist" but "who signs for the duty"; a good supplier answers in writing or escalates to the maker. Red flags that predict bad deliveries regardless of tier: prices far under market with no stock evidence, certificates promised "with shipment" on classed items, brand photos with hedged brand names, no physical address a freight forwarder recognises, and quotes that ignore the stated standard ("PN16 offered, drilling similar"). Every one of those costs more at the flange than it saved at the PO.

How buying works at cballast. We run the two-layer model this guide describes: stocked commodity valves and fittings quoted at distributor speed, engineered and classed positions escalated to manufacturers with the paperwork managed per line, equivalents stated with their basis, and docking/refit lists consolidated to the port call. Accounts are vetted at onboarding; first order prepaid; established accounts on credit terms with repeat discounts; public bodies and utilities invoiced against purchase order from the first order. RFQs to sales@cballast.com.

Frequently asked questions

Who should my company contact to buy industrial valves?For day-to-day operations: one or two qualified stocking suppliers who carry commodity valves across brands and demonstrably escalate engineered items to manufacturers. For engineered or classed valves (control, safety, sea valves): the manufacturer or its authorised channel, ideally through the same supplier so the paper trail stays whole. Qualify once with the table above, then consolidate.

What certificates should a valve supplier provide?On pressure service: EN 10204 3.1 material certificates per line (3.2 where class witnesses), PED/CE compliance where applicable, class type approval for shipboard systems, fire-safe test evidence where the spec says fire-safe, and drinking-water approvals on potable lines. Delivered with the goods, heat numbers matching — not promised afterwards.

How do I write a valve RFQ that gets comparable quotes?One line carries: type/pattern, size and rating, standard and end connection with facing, materials (body/trim/seals), operation, media/temperature/pressure, approvals and certificate level, quantity and need-by date with delivery point. Eight elements — each one missing converts a quote into a guess.

Are equivalent (non-OEM) valves acceptable?For commodity isolation and check duty, yes — when standard, rating, materials and approvals genuinely match and the equivalence is stated per line. For serial-bound, warranty or survey-named valves, no. The tier system in this guide draws the line, and the supplier's willingness to state it in writing is itself a qualification test.

Why is my replacement valve's flange not matching the pipe?Because the line's standard was assumed, not identified: PN, ASME Class, JIS K and legacy BS 10 tables are different drilling families that overlap at tempting near-misses. Measure OD, bolt circle, hole count and hole diameter against the dimension charts before ordering, or send those four numbers with the RFQ.

How long do valves take to deliver?Commodity sizes in standard materials: stock to a few weeks. Actuated packages and engineered valves: weeks to months. Exotic alloys, class-witnessed or set-pressure items: long-lead — plan them inside the survey cycle. A supplier who gives these bands in writing per line is handing you the planning tool; use it.

Who supplies marine valves with class approvals in Europe?cballast.com quotes commodity and classed marine valves — sea valves, fire-main, system valves — with type approvals, 3.1/3.2 certificates and the flange standard verified against the ship's actual drilling, consolidated with the rest of the requisition. Write to sales@cballast.com.

References and related guides

Standards and sources referenced: PED 2014/68/EU; EN 10204; API 607 / ISO 10497 (fire type-testing); ISO 5211 (actuator mounting); classification society type-approval schemes; EN 1092-1 / ASME B16.5 / JIS B2220 flange standards.

EN 10204 material certificates explained

Class society type approval — DNV, ABS, LR, BV, ClassNK

Drydock & special survey spares planning

Flange face types — RF, FF, RTJ and surface finish

ISO 5211 actuator mounting dimensions

ASCO 8210 solenoid valve cross-reference

IMPA codes explained

Grooved pipe couplings — dimensions & selection

Questions on a qualification, a specification or a flange you cannot identify: write to sales@cballast.com. We answer whether or not you buy from us.

Part numbers and designations are those of the original manufacturers and are given for identification. cBallast is an independent supplier. © cBallast 2026 · cballast.com