

Reflex Refix C-DE 80, discus-shaped expansion vessel, blue, 10/4 bar

Article number: 7270960

reflex

Thinking solutions.



Features

Type	C-DE 80
Colour	blue
Diaphragm material	butyl
Nominal volume	80 l
Max. useful volume	43,6 l
Max. permissible system temperature	70 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	10 bar
Factory provided gas supply pressure	4 bar
Connection	G 3/4"
Diameter	634 mm
Height	621 mm
Depth	338 mm
Projection water connection	135 mm
Tilt dimension approx.	887 mm
Weight	23,30 kg

Description

Refix C-DE

Non-flowed through diaphragm expansion tank for water supply installations that are not subject to DIN 1988, e.g. fire extinguishing and service water systems, underfloor heating or heat source installations. Approval according to the EU Pressure Equipment Directive 2014/68/EU. Vessels fitted according to DIN EN 13831. The high-quality butyl full diaphragm reliably separates the static gas filling from the water chamber.

- No medium circulating
- For antifreeze additive of at least 25 – 50 %
- Non-replaceable bladder according to DIN EN 13831
- Durable epoxy resin coating
- Parts in contact with water are corrosion-protected
- With stainless steel thread connection

