



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
															
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1400827	76	3	93	3,66	5	75	15	225	2,72	1,83	420	16,5	0,9	60	200
1388401	102	4	122	4,81	5	75	15	225	3,90	2,62	570	22,5	0,9	60	200
1388398	127	5	148	5,83	5	75	15	225	5,49	3,69	770	30,3	0,9	60	200
1388886	152	6	177	6,97	5	75	15	225	6,47	4,35	1070	42,2	0,9	60	200


IT

Tubo per aspirazione prodotti abrasivi

Applicazione: tubo spiralato con copertura grecata, per aspirazione e mandata di materiali abrasivi. Progettato per essere utilizzato nei sistemi di pulizia.

Temperatura: da -20°C a +70°C.

Costruzione

Sottostrato: nero, liscio in gomma SBR/NR antistatica, resistente all'abrasione.

Rinforzo: tessuti sintetici ad alta resistenza, spirale d'acciaio incorporata e treccia rame.

Copertura: nera, grecata (ad impressione tela), in gomma SBR/NR, antistatica, resistente all'abrasione ed agli agenti atmosferici.

EN

Abrasive suction hose

Application: hardwall square-corrugated hose, specially designed for suction of abrasive materials in clean-up systems.

Temperature: from -20°C (-4°F) to +70°C (+158°F).

Construction

Tube: black, smooth anti-static SBR/NR rubber, abrasion resistant.

Reinforcement: high strength synthetic cord, steel helix wire and copper wire.

Cover: black, square-corrugated (wrapped finish), SBR/NR anti-static rubber, abrasion and weathering resistant.