




**4-Hole 90° Flange with Male Metric Thread
and 24° Conical Bore (acc. to ISO 8434-1)
Type WP-LK-L/S**



PN ¹ (^{bar} / _{PSI})	Dimensions (^{mm} / _{in})				Series	D	F	G	P	Q	T (Metric)	ØK	Weight (^{kg} / _{lbs}) ca. per 100	Bolts	O-ring	Ordering Codes
8.8	ØLK	ØA	ØB	Metric												
315	35	14	10	L	8	57	39	16,5	37,5	16x1,5	6,4	18,4	2 x M6x22	20x2,5	WP-LK35-10L-W3-K	
4568	1.38	.55	.39		.31	2.24	1.54	.65	1.48		.25	40.48	2 x M6x35			
315	35	14	12	L	8	57	39	16,5	37,5	18x1,5	6,4	19,2	2 x M6x22	20x2,5	WP-LK35-12L-W3-K	
4568	1.38	.55	.47		.31	2.24	1.54	.65	1.48		.25	42.24	2 x M6x35			
250	35	14	15	L	8	56,5	39	16,5	37,5	22x1,5	6,4	20,2	2 x M6x22	20x2,5	WP-LK35-15L-W3-K	
3625	1.38	.55	.59		.31	2.22	1.54	.65	1.48		.25	44.44	2 x M6x35			
250	35	15	18	L	8	57	39	20	37,5	26x1,5	6,4	22,0	2 x M6x22	20x2,5	WP-LK35-18L-W3-K	
3625	1.38	.59	.71		.31	2.24	1.54	.79	1.48		.25	48.40	2 x M6x40			
315	35	15	16	S	8	57,5	39	20	38	24x1,5	6,4	25,3	2 x M6x22	20x2,5	WP-LK35-16S-W3-K	
4568	1.38	.59	.63		.31	2.26	1.54	.79	1.50		.25	55.66	2 x M6x40			
315	35	15	20	S	8	64,5	39	25	45	30x2	6,4	30,3	2 x M6x22	20x2,5	WP-LK35-20S-W3-K	
4568	1.38	.59	.79		.31	2.54	1.54	.98	1.77		.25	66.66	2 x M6x45			
100	40	20	15	L	9	58	42	22,5	37	22x1,5	6,4	26,0	4 x M6x22	26x2,5	WP-LK40-15L-W3-K	
1450	1.57	.79	.59		.35	2.28	1.65	.89	1.46		.25	57.14				
100	40	20	18	L	9	59	42	22,5	38	26x1,5	6,4	26,8	4 x M6x22	26x2,5	WP-LK40-18L-W3-K	
1450	1.57	.79	.71		.35	2.32	1.65	.89	1.50		.25	58.96				
100	40	20	22	L	9	59	42	22,5	38	30x2	6,4	26,7	4 x M6x22	26x2,5	WP-LK40-22L-W3-K	
1450	1.57	.79	.87		.35	2.32	1.65	.89	1.50		.25	58.84				
100	40	20	28	L	9	61	42	28	40	36x2	6,4	36,9	2 x M6x22	26x2,5	WP-LK40-28L-W3-K	
1450	1.57	.79	1.10		.35	2.40	1.65	1.10	1.57		.25	81.27	2 x M6x50			
100	40	20	35	L	9	62	42	34	41	45x2	6,4	40,6	2 x M6x22	26x2,5	WP-LK40-35L-W3-K	
1450	1.57	.79	1.38		.35	2.44	1.65	1.34	1.61		.25	89.32	2 x M6x60			
250	40	20	20	S	9	61	42	22,5	40	30x2	6,4	25,9	2 x M6x22	26x2,5	WP-LK40-20S-W3-K	
3625	1.57	.79	.79		.35	2.40	1.65	.89	1.57		.25	56.98	2 x M6x45			
100	55	26,5	35	L	12	78	58	32	49	45x2	8,4	76,6	2 x M8x25	32x2,5	WP-LK55-35L-W3-K	
1450	2.17	1.04	1.38		.47	3.07	2.28	1.26	1.93		.33	168.52	2 x M8x60			
100	55	26,5	42	L	12	78	58	40	49	52x2	8,4	103,6	2 x M8x25	32x2,5	WP-LK55-42L-W3-K	
1450	2.17	1.04	1.65		.47	3.07	2.28	1.57	1.93		.33	227.88	2 x M8x70			
250	55	18,2	20	S	13	69	58	24	45	30x2	8,4	61,7	2 x M8x25	32x2,5	WP-LK55-20S-W3-K	
3625	2.17	.72	.79		.51	2.72	2.28	.94	1.77		.33	135.70	2 x M8x50			
250	55	26,5	25	S	13	78	58	30	49	36x2	8,4	62,0	2 x M8x25	32x2,5	WP-LK55-25S-W3-K	
3625	2.17	1.04	.98		.51	3.07	2.28	1.18	1.93		.33	136.40	2 x M8x55			
250	55	26,5	30	S	12	78	58	32	49	42x2	8,4	63,2	2 x M8x25	32x2,5	WP-LK55-30S-W3-K	
3625	2.17	1.04	1.18		.47	3.07	2.28	1.26	1.93		.33	139.04	2 x M8x50			

¹ The maximum working pressure PN (bar/PSI) applies only to the flange itself. The actual maximum working pressure depends on the thickness and the quality of the tube used.

Materials / Ordering Options / Examples

* Kit with 4-Hole Flange made of Steel S355J0 or equivalent, zinc/nickel-plated including Metric bolts 8.8, spring rings, O-ring made of NBR (Buna-N®)

WP-LK...-...-W3-K

Please always indicate ØLK, ØB and Series.

