

CORRUFLEX BUNA

Code 4430



I. Diam. Toll. EN ISO 1307 [mm]	E. Diam. [mm]	Pitch [mm]	Weight +/-5% [g/m]	PN/bar at 20°C [bar]	Coil maximum length [m]
10		5,5			
12		6,0			
13		6,0			
14		6,0			
16		6,5			
18		7,0			
19		7,0			
20		7,0			
22		7,0			
25	32	7,5	330	6,5	50
28		8,0			
30		8,0			
32	40	8,0	440	6	50
35		8,5			
38	46	8,5	520	5,5	50
40	48	8,5	560	5,5	50
42		8,5			
45	64	8,5	730	5	50
51	60	9,5	880	4,5	50
55		10,0			
60	70	10,0	1070	4	50
63	73	10,25	1130	4	50
70		10,5			
76	88	11,0	1420	3,5	50
80		11,0			
90	103	13,0	1850	3	50
102	116	13,0	2400	2,5	50
110	124	13,0	2750	2,5	50
120		13,0			
127	142	15,0	3270	2	30
130		15,0			
140		15,5			
152	168	15,5	4300	1,5	30
160		15,5			
180		15,5			
203	224	20,0	6500	1	10
254	280	24,0	10200	1	10
305	330	28,0	12200	1	10

Description:

new design construction

**PVC/NBR suction/
discharge hose**

for industrial water, waste-water,
dung, mineral oils a.o. under
medium duty conditions.

PVC/NBR compound with
polymeric softeners and a special
designed rigid PVC profile,
offering an extremely flexible hose
also under cold conditions.

Vacuum:

0,9 bar

Temperature range:

-30 °C / +65 °C

Construction:

Black PVC/NBR with blue spiral,
inside smooth, outside corrugated.

Bending radius:

2 x inside diameter

