

Complete Parts
 For Flare Couplings 37° and Coupling Bodies with
 24°-Cone
 Type of Port End W DIN 3861



(1) In the 315 bar section, the normal safety factor of 4:1
 is reduced to 3:1.

Pressure	Tube O.D.	Thread	Approx. Dimensions					Order-Code
PN	D1 + Tol.	G	d	L	L1	L2	SW	

Series L

500	6	M 12 x 1,5	3	17,0	11,5	10,5	14	BAN-06-L
500	8	M 14 x 1,5	5	18,0	12,0	11,0	17	BAN-08-L
500	10	M 16 x 1,5	6	19,5	12,5	12,5	19	BAN-10-L
400	12	M 18 x 1,5	8	20,5	12,5	13,0	22	BAN-12-L
400	15	M 22 x 1,5	11	23,0	12,5	14,0	27	BAN-15-L
400	18	M 26 x 1,5	14	23,0	13,0	14,5	32	BAN-18-L
315	22	M 30 x 2	17	27,5	14,2	18,0	36	BAN-22-L
250	28	M 36 x 2	23	27,5	14,7	17,0	41	BAN-28-L
250	35	M 45 X 2	28	30,0	18,5	19,0	50	BAN-35-L
250	42	M 52 x 2	35	34,0	20,5	21,0	60	BAN-42-L

Series S

800	6	M 14 x 1,5	3	18,0	11,5	10,5	17	BAN-06-S
800	8	M 16 x 1,5	5	20,0	12,0	11,0	19	BAN-08-S
800	10	M 18 x 1,5	6	20,5	12,5	12,5	22	BAN-10-S
630	12	M 20 x 1,5	8	21,0	12,5	13,0	24	BAN-12-S
630	14	M 22 x 1,5	9	23,0	14,0	14,5	27	BAN-14-S
630	16	M 24 x 1,5	11	26,5	15,0	17,0	30	BAN-16-S
420	20	M 30 x 2	14	27,5	18,5	17,5	36	BAN-20-S
420	25	M 36 x 2	19	30,5	20,0	20,0	46	BAN-25-S
420	30	M 42 x 2	23	32,0	22,0	21,5	50	BAN-30-S
420 (1)	38	M 52 x 2	30	38,0	26,0	26,5	60	BAN-38-S