


Rundhovedet – Alu/Stål – Åben – PEEL - Banan



MFX 1301

Ø d	l (+1/-0,2)	Nitte evne	Beskrivelse	Ø d _k	k	Ø d _m	p	Træk (N)	Snit (N)
mm	mm	mm		mm	mm	mm	mm		
3,2	8,0	0,5-1,0	1301 3208	6,5 +/-0,2	1,0 +/-0,1	~1,80	≥27	750	820
(+/-0,15)	10,0	1,0-3,0	1301 3210						
	12,0	3,0-5,0	1301 3212						
Ø3,5 min.	16,0	7,0-9,0	1301 3216						
Ø3,7 maks.	18,0	9,0-11,0	1301 3218						
4,0	10,0	1,5-5,0	1301 4010	8,0 +/-0,4	1,2 +/-0,2	~2,10	≥27	1140	1280
(+/-0,15)	12,0	4,0-6,5	1301 4012						
	14,0	6,0-9,0	1301 4014						
Ø4,3 min.	16,0	8,0-11,0	1301 4016						
Ø4,5 maks.	18,0	10,0-13,0	1301 4018						
	20,0	12,0-15,0	1301 4020						
4,8	10,0	1,5-4,0	1301 4810	9,0 +/-0,4	1,4 +/-0,2	~2,70	≥27	2450	2100
(+/-0,15)	12,0	2,0-6,0	1301 4812						
	14,0	4,0-8,0	1301 4814						
Ø5,2 min.	16,0	6,0-10,0	1301 4816						
Ø5,3 maks.	18,0	8,0-12,0	1301 4818						
	20,0	10,0-14,0	1301 4820						
	22,0	12,0-16,0	1301 4822						
	25,0	16,0-19,0	1301 4825						
	30,0	19,0-24,0	1301 4830						
	35,0	24,0-29,0	1301 4835						
	40,0	29,0-34,0	1301 4840						