


For Fittings with 24°-Cone and Solderless Connectors
 DIN 2353 / DIN EN ISO 8434-1
 Light Series = DKOS - 90°
 O-ring = NBR
 On Request: Viton



Hose	Bore	Thread	Tube O.D.	Approx. Dimensions					Order-Code
DN	in.	G	D	A	B	C	SW		
05	3/16"	M 12 x 1,5	6	28,0	37,0	3,0	14		DKOL-06-90°-DN 05
06	1/4"	M 12 x 1,5	6	28,0	28,5	4,0	14		DKOL-06-90°-DN 06
05	3/16"	M 14 x 1,5	8	28,0	28,5	3,0	17		DKOL-08-90°-DN 05
06	1/4"	M 14 x 1,5	8	28,5	29,5	4,0	17		DKOL-08-90°-DN 06
08	5/16"	M 14 x 1,5	8	35,0	47,0	4,5	17		DKOL-08-90°-DN 08
06	1/4"	M 16 x 1,5	10	28,5	29,5	4,0	19		DKOL-10-90°-DN 06
08	5/16"	M 16 x 1,5	10	31,5	39,0	5,5	19		DKOL-10-90°-DN 08
10	3/8"	M 16 x 1,5	10	35,0	37,5	7,0	19		DKOL-10-90°-DN 10
06	1/4"	M 18 x 1,5	12	29,0	33,5	4,0	22		DKOL-12-90°-DN 06
08	5/16"	M 18 x 1,5	12	34,5	37,0	5,5	22		DKOL-12-90°-DN 08
10	3/8"	M 18 x 1,5	12	34,0	38,0	7,0	22		DKOL-12-90°-DN 10
12	1/2"	M 18 x 1,5	12	45,0	53,0	8,5	22		DKOL-12-90°-DN 12
10	3/8"	M 22 x 1,5	15	42,5	41,5	7,0	27		DKOL-15-90°-DN 10
12	1/2"	M 22 x 1,5	15	44,0	43,0	9,5	27		DKOL-15-90°-DN 12
12	1/2"	M 26 x 1,5	18	46,5	51,0	9,5	32		DKOL-18-90°-DN 12
16	5/8"	M 26 x 1,5	18	56,0	52,0	12,5	32		DKOL-18-90°-DN 16
19	3/4"	M 26 x 1,5	18	59,0	70,0	13,0	32		DKOL-18-90°-DN 19
16	5/8"	M 30 x 2	22	57,0	63,5	12,0	36		DKOL-22-90°-DN 16
19	3/4"	M 30 x 2	22	61,0	58,0	14,5	36		DKOL-22-90°-DN 19
19	3/4"	M 36 x 2	28	70,0	62,5	14,5	41		DKOL-28-90°-DN 19
25	1"	M 36 x 2	28	82,0	70,0	20,0	41		DKOL-28-90°-DN 25
31	1 1/4"	M 45 x 2	35	87,0	85,0	25,0	50		DKOL-35-90°-DN 31
38	1 1/2"	M 45 x 2	35	105,0	114,0	28,0	50		DKOL-35-90°-DN 38
31	1 1/4"	M 52 x 2	42	101,5	97,0	25,0	60		DKOL-42-90°-DN 31
38	1 1/2"	M 52 x 2	42	104,0	103,0	31,0	60		DKOL-42-90°-DN 38