

Master-PUR L Food

PU Suction & Transport Hose, light duty, food-grade quality acc. to EU 10/2011 and FDA



Technical Drawing



Connections



Construction



Material

- spiral: spring steel wire (stainless steel 1.4310)
- wall: pure polyether polyurethane, food-grade quality (FDA)
- wall thickness between spirals approx. 0.7 mm

Applications

- Pharmaceutical industry
- Chemicals industry
- Food industry

Properties

- The hose conforms with EU Guideline 10/2011
- Approved for food-grade categories: A, B, C, D1, D2, E (contact durations acc. to Test Report)
- materials comply with the following food regulations:
 - FDA 21 CFR §177.2600
 - FDA 21 CFR §178.2010

- ## Temperature Range

- Product Variations (**Please replace “x” with your desired hose length.)

[illegible]

180	0,42	0,15	190	190	1,9	110-180-501	000012:180:x	/	25
200	0,42	0,15	212	211	2,25	110-200-501	000012:200:x	/	25
203	0,42	0,15	215	214	2,3	110-203-501	000012:203:x	5/10	25

All data refers to a medium and ambient temperature of +20 °C.
* Refers to the inner hose lining
Subject to technical changes and colour deviations.

Available on request

- Available on request in other lengths, sizes and colours, with print.