

Worker Adjustable

Fall Arrest line 1215



- Work on roof
- Adjustable
- 140 kg user weight

012202705 5 m

012202710 10 m

012202715 15 m

DESCRIPTION

This fall arrest line is made of a 12 mm thick rope of high quality, and the adjustable rope lock allows the product to be used easily in, for example, roof work. The fall arrest line is tested and approved for users up to 140 kg. The textile fall arrester is located in an openable bag to make it easier to carry out an annual inspection according to EN 365.

TECHNICAL SPECIFICATION

Physical properties

Lanyard: 12 mm patron kernmantel rope

Lanyard strength: >25 kN

Energy absorber: Yes textile

Structure attaching connector: 9673 Twist lock aluminium

Body attaching connector: 9673 Twist lock aluminium

Product weight: 1,65 Kg-2,58 Kg

Segments

User applications: General industri

Standards

Standards: EN 353-2

Notified Body: Nr 0402: RISE, Box 857, SE-501 15 Borås
Sweden

Declaration of Conformity: Yes

Lifespan and other information

Lifespan: 10+2 år

Maximum user weight:

140 Kg

Inspection:

Annual inspection by competent person

Identification:

Serial number

Manual languages:

EN, SV, NO, DA, FI, DE, FR, ES



Lägatan 63, 302 63 Halmstad, Sweden
Tel. +46 (0)35 710 75 00
support@crestogroup.com | www.crestogroup.com