

**Reflex Servitec 35, 90°C,
vacuum spray deaeration/make-up unit
Article-No.:8831100**



Reflex Servitec

Vacuum spray tube degassing for system and makeup water degassing in closed heating and cooling circuits, configured as a fully automatic multi-function unit with 'auto-start' function and automatic hydraulic compensation of the degassing process and monitoring of the makeup function. Suitable for the media water and water/glycol mixtures up to a mixing ratio of 50/50%.

Functional unit comprising a hydraulic part and a Control Basic operating unit. Both are ergonomically combined in an easy-to-maintain modular floor-standing framework system made of EV 1 anodized aluminium precision sections. Degassing takes place within the hydraulic part using a stainless steel diaphragm pump in conjunction with a vertically arranged stainless steel vacuum spray tube. This is equipped with a vacuum spray nozzle, dipstick-tube degassing unit and pressure/level monitoring.

The Control Basic control unit is

integrated in a robust plastic housing in which both the power and communication electronics and the control panel with dirt-resistant membrane-covered keyboard is housed.

Control Basic is a fully automatic, freely configurable microprocessor control with real-time clock, differentiating error and parameter memory, two line plain text display for system pressure, tank filling level and all relevant operating and fault messages, LED display for operating modes and general error messaging.

Communication electronics comprising:

- RS 485 port as data interface or for the connection of optional communication components
- Potential-free output for the forwarding of the collective message
- Digital input for signal processing of a contact water meter
- Input for makeup functional request via external signal

Control unit completely assembled and

wired ready for connection according to VDE regulations, mains power cable and mains plug, system connections by means of integrated shut-off valves.

Vacuum spray degassing of the content, filling and make-up water in self-optimising operation with cycles for continuous, interval and make-up degassing. Controlled make-up via reliable two-way motorised ball valve. Actuation takes place via an integrated system pressure interpretation unit or an external 230 V signal (e.g. a pressure maintenance station) with automatic interruption and fault messaging upon exceeding of the running time and/or the number of cycles. Alternatively, make-up can be performed from an open system separator vessel. Evaluation option provided by a contact water meter including optional possible capacity monitoring of ion exchangers in the make-up pipe. Documentation and control of the entire system in respect of the above mentioned parameters.

Merkmale

Type: 35

adm. excess oper. press.: 8 bar

adm. operating temp.: 90 °C

adm. ambient temp.: >0..35 °C

sound level: < 55 dB(A)

power supply: 230V/50Hz

electr. power cons.: 0,75 kW

electr. nominal curr.: 5,00 A

depth x width x height (mm): 486/553/965

empty weight: 42,0 kg

connections pressure-side: G 1"

flow-off side: G 1/2"

make-up: G 1/2"

elimin. degree dissolved gases: up to 90%

part. vol.flow netw. up to: 0,550 m³/h

make-up volume flow up to: 0,350 m³/h

water content: I

heat generator SV: bar

advance press. exp. vessel: bar

final press. press.maint.: bar

min. flow press. make-up: bar



09.09.2020 18:02

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de

Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen