



XY2CE2A250



XY2CE1A450



XY2CE2A450



XY2CE2A296



XY2CE1A296H7



Emergency stop rope pull switch with window for viewing the cable tension

Emergency stop rope pull switches with single anchor point ISO M20 or Pg 13.5 (1) and 1/2" NPT (2)

Turnbuckle or quick tensioner, cable, and end spring to be ordered separately (3)

Without pilot light

Cable length	Colors and materials	Reset	Supply voltage	Contact type	Cable anchor point	Reference	Weight kg
≤ 70 m	Zamak red RAL 3000 body Stainless steel cover Nitrile bellows	By flush pushbutton	—	1 1 NC + NO slow break	RH side	XY2CE1A150 (2)	1.450
					LH side	XY2CE2A150 (2)	1.450
					RH side	XY2CE1A250 (2)	1.450
					LH side	XY2CE2A250 (2)	1.450
		By booted pushbutton	—	1 1 NC + NO slow break	RH side	XY2CE1A270 (2)	1.450
					LH side	XY2CE2A270 (2)	1.450
					RH side	XY2CE1A290 (2)	1.450
					LH side	XY2CE2A290 (2)	1.450
		By key switch (key no. 421)	—	1 1 NC + NO slow break	RH side	XY2CE1A450	1.465
					LH side	XY2CE2A450 (2)	1.465
					RH side	XY2CE1A470	1.470
					LH side	XY2CE2A470	1.470

With yellow LED pilot light (direct supply)

≤ 70 m	Zamak red RAL 3000 body Stainless steel cover Nitrile bellows	By booted pushbutton	24 to 130 V ~/-	2 2 NC + NO slow break	RH side	XY2CE1A296 (2)	1.470
					LH side	XY2CE2A296 (2)	1.470
			230 to 240 V ~	2 2 NC + NO slow break	RH side	XY2CE1A297 (2)	1.470
					LH side	XY2CE2A297 (2)	1.470

Other versions

- ATEX versions
 - Versions with low tripping force (< 125 N). Rope pull tripping deflection < 300 mm
 - Versions with reset by Ø 30 mm mushroom head pushbutton
 - Versions with cable tension viewing window for adjustment when the cover is closed
 - Versions with silicon bellows
- Please contact our Customer Care Center.

(1) With untapped entries for ISO M20 or Pg 13.5 cable gland.

(2) For 1/2" NPT tapped cable entry version, add H7 to the end of the selected reference (for these versions, the pilot light is red).
For example: XY2CE1A250 becomes XY2CE1A250H7.

(3) See separate parts on [page 12](#).