

PRODUCT NUMBER: 1013047

Laser Lite LS-400 Refill



+ Visa fler

Översikt

Reference Number

1013047

Product Type

Hörselskydd

Range

Earplugs

Line

Disposable Earplugs

Brand

Howard Leight by Honeywell

Industry

- Administration • Agriculture • Army - Defence • ATEX environment • Automotive and Part Manufacturer
- Aviation • Building and Construction • Catering • Chemical Industries • Energy or Electricity
- Fire Protection brigades • Fishing • Food Industries • Foundry • Glass Industries
- Green Spaces • Homeland defense • Industrial Cleaning • Iron and steel industry
- Logistics • Maintenance • Medical and Pharmaceutical • Metal steel • Mining and Quarrying
- Offshore • Paper Industries • Petro-chemical • Printing Industries • Services
- Telecoms • Textile Industries • Transportation • Utilities • Water treatment • Welding

• Wood Industries • Laboratory • Ship Building • Industry

Product Use

Laser Lite LS-400 Dispenser Refill, Disposable

Features & Benefits**Feature**

VIBRANT COLOURS Makes protection fun – and highly visible. SELF-ADJUSTING FOAM Polyurethane foam adjusts to fit virtually every wearer. CONTOURED T-SHAPE Aids in easy insertion, removal from ear canal.

Benefit

The bright idea in hearing protection, Laser Lite's low-pressure foam expands gently inside the ear canal for comfortable long-term wear, while its contoured T-shape delivers easy handling. Its high visibility magenta and yellow colors make compliance checks quick and easy. Plus, Laser Lite is available with special packaging and dispenser options, ideal for process industries with low tolerances for packaging waste.

Technical Description**SNR (dB)**

35

H (dB)

34

M (dB)

32

L (dB)

31

Attenuation Data

Frequency (Hz) Frequenz (Hz) Fréquence (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)	33.4	34.1	35.5	37.6	34.9	35.7	42.5	44.1
Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB)	4.6	4.7	4.6	4.1	5.0	2.8	2.9	4.2
Assumed Protection (dB) Angenommener (dB) Protection supposé (dB)	28.8	29.4	30.9	33.5	29.9	32.9	39.6	39.9

Size

Fits All

Color

Yellow and Magenta

Shape

T

Corded

No

Weight (grs)

0.48

Certifications

 **E.C. Declaration of Conformity**

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

951095

EC Attestation

 EC Attestation

EC Attestation Number

9503632 & 200822449

Trycksaker & dokument

 **E.C. Declaration of Conformity**

 PIC SKU - Pictures

<http://www.honeywellsafety.com/assets/0/324/500/51887/b0b16555aedd42f89c634480a0c67b17.jpg>

Foton & bilder

Det finns inga bilder för närvarande.

Maintenance

Life Cycle

These plugs must be disposed of and replaced after each wearing.

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.

Packaging

EAN Code

033552014324



Välj region/land

© 2011 Honeywell International Inc.