


Rundhovedet – Stål/Stål - Lukket



MFX 1241

Ø d	l (+1/-0,2)	Nitte evne	Beskrivelse	Ø d _k	k	Ø d _m	p	Træk (N)	Snit (N)
mm	mm	mm		mm	mm	mm	mm		
3,2	6,0	0,5-1,5	1241 3206						
(+0,08/-0,10)	8,0	1,5-3,0	1241 3208	6,0	1,0	~1,90	≥27	2200	1600
	9,5	3,0-5,0	1241 3209	+/-0,24	+/-0,3				
Ø3,3	12,0	5,0-7,0	1241 3212						
4,0	6,0	0,5-1,5	1241 4006						
(+0,08/-0,10)	8,0	1,5-3,0	1241 4008						
	10,0	3,0-5,0	1241 4010	8,0	1,4	~2,30	≥27	2500	2300
Ø4,1	12,0	5,0-6,5	1241 4012	+/-0,29	+/-0,3				
	15,0	6,5-10,5	1241 4015						
4,8	8,0	1,0-3,0	1241 4808						
(+0,08/-0,10)	9,5	3,0-5,0	1241 4809	9,5	1,7	~2,90	≥27	3800	2900
	12,0	5,0-6,5	1241 4812	+/-0,29	+/-0,3				
Ø4,9	16,0	6,5-10,5	1241 4816						