

FRIGA-BOHN - -

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com

FRIGA-BOHNItem : **Item 16**Typ : **Dual discharge**

Date 11/30/2023

Version : 4.17

NTA C 3R 2-EC V1 CO2 60b**Total capacity : 5.43 kW****DT1 (Dew) / DTM (Mean) : 8 / 8 K****Operating conditions**

Refrigerant :	CO2
Room temperature :	4 °C
Unit number :	1
Pressure :	-1 bar / 60 bar

Aeraulic characteristics (per unit)

Nb. and diameter of fans :	2 x 350 mm
Air flow-rate :	2920 m3/h
Pressure :	0 Pa
Air throw :	2 x 13 m
Lp (at 4m) :	35 dB(A)

Coil characteristics (per unit)

Surface :	17.4 m²
Volume :	2.5 dm3
Fin spacing :	3.5 mm
Inlet / Outlet :	1/2"-5/8" (D)

Electrical characteristics (per unit)

Rotation speed :	1100 tr/min
Maximum input power :	2 x 80 W
Maximum operating current :	2 x 0.7 A
Motor coupling :	-
Voltage/ Nb Phases / Frequency :	230V / 1 / 50-60Hz

Dimensional characteristics (per unit)

Dimensions (L/D/H) :	1372/819/299 mm
Empty net weight :	30 kg
Packaging (L/D/H) :	1480 / 890 / 500 mm
Packed unit weight :	42 kg
Standard packaging :	Cardboard on pallet

Rotation speed	Total capacity	Air flow-rate	Air throw	Lp (at 4m)
1100	5.43	2920	2 x 13	35
900	4.79	2410	2 x 11	32
750	4.39	2120	2 x 10	26
650	3.94	1810	2 x 9	25

(1) The average acoustic pressure level in dB(A) measured at 4 m, at fan height, in direct line of sight on a reflective surface, are given as an example. Only the acoustic pressure spectrum and Lw value, are contractually binding and may be used to evalu

All prices are retail prices 2023. Our proposals, quotes and order acceptances are subject to our general terms of sale.

FRIGA-BOHN - -

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com

FRIGA-BOHN

Item : **Item 16**

Typ : **Dual discharge**

Date 11/30/2023

Version : 4.17

Model : NTA C 3R 2-EC V1 CO2 60b

(Drawings are only indicative)

