


PLIA – Multigrip – Rundhovedet – Alu/Stål



MFX 1001

Ø d	l (+1/-0,2)	Nitte evne	Beskrivelse	Ø d _k	k	Ø d _m	p	Træk (N)	Snit (N)
mm	mm	mm		mm	mm	mm	mm		
3,0	6,0	0,5-3,0	1001 3006	6,0 +/-0,24	≤1,4	~1,7	≥27	655	520
(+0,05/-0,13)	8,0	0,5-5,0	1001 3008						
	10,0	2,5-7,0	1001 3010						
Ø3,1 (3,3 maks)	12,0	4,5-9,0	1001 3012						
3,2	6,0	0,5 3,0	1001 3206	6,0 +/-0,24	≤1,4	~1,78	≥27	980	680
(+0,05/-0,13)	8,0	0,5-5,0	1001 3208						
	9,5	2,0-6,5	1001 3209						
Ø3,3 (3,5 maks)	10,0	2,5-7,0	1001 3210						
	11,1	3,5-8,0	1001 3211						
	12,0	4,5-9,0	1001 3212						
	12,7	5,5-9,5	1001 3213						
	14,0	6,5-11,0	1001 3214						
	16,0	8,5-13,0	1001 3216						
4,0	6,0	0,5-2,5	1001 4006	8 +/-0,29	≤1,7	~2,18	≥27	1600	1150
(+0,05/-0,13)	8,0	0,5-4,5	1001 4008						
	9,5	1,0-6,0	1001 4009						
Ø4,1 (4,3 maks)	10,0	1,5-6,5	1001 4010						
	12,0	3,5-8,5	1001 4012						
	12,7	4,0-9,5	1001 4013						
	14,0	5,5-10,5	1001 4014						
	16,0	7,5-12,5	1001 4016						
	17,0	8,5-13,5	1001 4017						
	18,0	9,5-14,5	1001 4018						
	20,0	11,5-16,5	1001 4020						
4,8	10,0	0,5-5,0	1001 4810	9,5 +/-0,29	≤2,0	~2,78	≥27	2350	1500
(+0,05/-0,13)	10,3	0,5-5,5	1001 4811						
	12,0	2,0-7,0	1001 4812						
Ø4,9 (5,2 maks)	14,0	4,0-9,0	1001 4814						
	15,1	5,0-10,5	1001 4815						
	16,0	6,0-11,0	1001 4816						
	17,0	7,0-12,0	1001 4817						
	18,0	8,0-13,0	1001 4818						
	20,0	10,0-15,0	1001 4820						
	22,0	12,0-17,0	1001 4822						
	24,0	14,0-19,0	1001 4824						
	24,8	14,5-19,5	1001 4825						