

APDatec 18A



Flat-hose from Polyester-fabric, inside PVC-coated, completed with Storz-couplings

For pumping of water for example during floods or in constructions. As pressure-hose after the pumps in flood-boxes.

Material

Soft-PVC

Yarn

Polyester fabric

Colour

white

Temperature

-20°C/+65°C

Durability

refer to Soft PVC

Imprint

with imprint

REACH

conformity to 1907/2006/EC

RoHS

conformity to RoHS

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 18A

Nr.	Inside Diameter in mm	kg/Piece	Working Pressure bar	Bursting Pressure bar	Length in m
18200	51	4,64	10	30	20
18201	76	7,7	10	30	20
18202	102	11,9	7	21	20
18203	51	6,64	10	30	30
18204	51	2,64	10	30	10
18205	51	5,64	10	30	25
18206	51	3,64	10	30	15
18207	76	4,51	10	30	10
18208	76	6,11	10	30	15
18209	76	9,3	10	30	25
18210	76	10,9	10	30	30
18211	102	7,5	7	21	10
18212	25	1,1	10	30	10
18213	25	2	10	30	20
18214	25	2,9	10	30	30
18215	25	0,65	8	24	5
18216	51	1,644	8	24	5
18217	76	2,535	8	24	5
18218	102	5,12	7	21	5
18219	102	9,32	7	21	15
18223	102	15,62	7	21	30
18224	25	1,55	10	30	15
18225	25	2,45	10	30	25
18226	102	13,52	7	21	25