



Angled Weld Plate Type WSP



STAUFF Group 1

STAUFF Group 1A to 6

Ordering Codes

Weld Plate



***WSP-*1-*M-*W1**

* Angled Weld Plate	WSP
* STAUFF Group	1
* Thread code	Metric ISO thread M Unified coarse (UNC) thread U
* Material code	Carbon Steel, zinc/nickel-plated W3 Stainless Steel V2A W4 1.4301 / 1.4305 (AISI 304 / 303) Stainless Steel V4A W5 1.4401 / 1.4571 (AISI 316 / 316 Ti)

Group STAUFF	DIN	Dimensions (mm/in)	Thread G	L1	L2	B1	B2	S	H	ØD1	ØD2	Ordering Codes (Standard Options)
1	0	M6		30	14	30	30	3	6,5	12	6,5	WSP-1-M-W1
		1/4-20 UNC		1.18	.55	1.18	1.18	.12	.26	.47	.26	WSP-1-U-W1
1A	1	M6		36	20	30	30	3	6,5	12	6,5	WSP-1A-M-W1
		1/4-20 UNC		1.26	.79	1.18	1.18	.12	.26	.47	.26	WSP-1A-U-W1
2	2	M6		42	26	30	30	3	6,5	12	6,5	WSP-2-M-W1
		1/4-20 UNC		1.65	1.02	1.18	1.18	.12	.26	.47	.26	WSP-2-U-W1
3	3	M6		50	33	30	30	3	6,5	12	6,5	WSP-3-M-W1
		1/4-20 UNC		1.97	1.30	1.18	1.18	.12	.26	.47	.26	WSP-3-U-W1
4	4	M6		60	40	30	30	3	6,5	12	6,5	WSP-4-M-W1
		1/4-20 UNC		2.36	1.57	1.18	1.18	.12	.26	.47	.26	WSP-4-U-W1
5	5	M6		70	52	30	30	3	6,5	12	6,5	WSP-5-M-W1
		1/4-20 UNC		2.76	2.05	1.18	1.18	.12	.26	.47	.26	WSP-5-U-W1
6	6	M6		88	66	30	30	3	6,5	12	6,5	WSP-6-M-W1
		1/4-20 UNC		3.46	2.60	1.18	1.18	.12	.26	.47	.26	WSP-6-U-W1

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Bridge Weld Plate Type BSP



Ordering Codes

Weld Plate

***BSP-*1A-*M-*W1**

* Bridge Weld Plate	BSP
* STAUFF Group	1A
* Thread code	Metric ISO thread M Unified coarse (UNC) thread U
* Material code	Carbon Steel, phosphated W2 Carbon Steel, zinc/nickel-plated W3 Stainless Steel V2A W4 1.4301 / 1.4305 (AISI 304 / 303) Stainless Steel V4A W5 1.4401 / 1.4571 (AISI 316 / 316 Ti)

Group STAUFF	DIN	Dimensions (mm/in)	Thread G	L1	L2	B	S	H1	H2	ØD	Ordering Codes (Standard Options)
1A	1	M6		48	20	30	3	13	6,5	12	BSP-1A-M-W1
		1/4-20 UNC		1.89	.79	1.18	.12	.52	.26	.47	BSP-1A-U-W1
2	2	M6		54	26	30	3	13	6,5	12	BSP-2-M-W1
		1/4-20 UNC		2.13	1.02	1.18	.12	.52	.26	.47	BSP-2-U-W1
3	3	M6		62	33	30	3	13	6,5	12	BSP-3-M-W1
		1/4-20 UNC		2.44	1.30	1.18	.12	.52	.26	.47	BSP-3-U-W1
4	4	M6		71	40	30	3	13	6,5	12	BSP-4-M-W1
		1/4-20 UNC		2.80	1.57	1.18	.12	.52	.26	.47	BSP-4-U-W1
5	5	M6		85	52	30	3	13	6,5	12	BSP-5-M-W1
		1/4-20 UNC		3.35	2.05	1.18	.12	.52	.26	.47	BSP-5-U-W1
6	6	M6		98	66	30	3	13	6,5	12	BSP-6-M-W1
		1/4-20 UNC		3.86	2.60	1.18	.12	.52	.26	.47	BSP-6-U-W1

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

