



power contactor, AC-3e/AC-3, 80 A, 37 kW / 400 V, 3-pole, 24 V DC, 0.8-1.2\* Us, with integrated varistor, auxiliary contacts: 1 NO + 1 NC, screw terminal, size: S2, suitable for PLC outputs

|                                                                                                              |                                                        |
|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| product brand name                                                                                           | SIRIUS                                                 |
| product designation                                                                                          | Coupling contactor                                     |
| product type designation                                                                                     | 3RT2                                                   |
| <b>General technical data</b>                                                                                |                                                        |
| size of contactor                                                                                            | S2                                                     |
| product extension                                                                                            |                                                        |
| • function module for communication                                                                          | No                                                     |
| • auxiliary switch                                                                                           | Yes                                                    |
| power loss [W] for rated value of the current                                                                |                                                        |
| • at AC in hot operating state                                                                               | 17.1 W                                                 |
| • at AC in hot operating state per pole                                                                      | 5.7 W                                                  |
| • without load current share typical                                                                         | 1 W                                                    |
| insulation voltage                                                                                           |                                                        |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                                                  |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                                                  |
| surge voltage resistance                                                                                     |                                                        |
| • of main circuit rated value                                                                                | 6 kV                                                   |
| • of auxiliary circuit rated value                                                                           | 6 kV                                                   |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                                                  |
| shock resistance at rectangular impulse                                                                      |                                                        |
| • at DC                                                                                                      | 7.7g / 5 ms, 4.5g / 10 ms                              |
| shock resistance with sine pulse                                                                             |                                                        |
| • at DC                                                                                                      | 12g / 5 ms, 7g / 10 ms                                 |
| mechanical service life (operating cycles)                                                                   |                                                        |
| • of contactor typical                                                                                       | 10 000 000                                             |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                                              |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                                             |
| reference code according to IEC 81346-2                                                                      | Q                                                      |
| Substance Prohibitance (Date)                                                                                | 10/01/2014                                             |
| SVHC substance name                                                                                          | Blei - 7439-92-1<br>Bleimonoxid (Bleioxid) - 1317-36-8 |
| <b>Ambient conditions</b>                                                                                    |                                                        |
| installation altitude at height above sea level maximum                                                      | 2 000 m                                                |
| ambient temperature                                                                                          |                                                        |
| • during operation                                                                                           | -25 ... +60 °C                                         |
| • during storage                                                                                             | -55 ... +80 °C                                         |
| relative humidity minimum                                                                                    | 10 %                                                   |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum                                               | 95 %                                                   |

| Environmental footprint                                           |                    |
|-------------------------------------------------------------------|--------------------|
| Environmental Product Declaration(EPD)                            | Yes                |
| Global Warming Potential [CO2 eq] total                           | 107 kg             |
| Global Warming Potential [CO2 eq] during manufacturing            | 5.88 kg            |
| Global Warming Potential [CO2 eq] during operation                | 102 kg             |
| global warming potential [CO2 eq] after end of life               | -0.988 kg          |
| Main circuit                                                      |                    |
| number of poles for main current circuit                          | 3                  |
| number of NO contacts for main contacts                           | 3                  |
| operating voltage                                                 |                    |
| • at AC-3 rated value maximum                                     | 690 V              |
| • at AC-3e rated value maximum                                    | 690 V              |
| operational current                                               |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value       | 90 A               |
| • at AC-1                                                         |                    |
| — up to 690 V at ambient temperature 40 °C rated value            | 90 A               |
| — up to 690 V at ambient temperature 60 °C rated value            | 80 A               |
| • at AC-3                                                         |                    |
| — at 400 V rated value                                            | 80 A               |
| — at 500 V rated value                                            | 80 A               |
| — at 690 V rated value                                            | 58 A               |
| • at AC-3e                                                        |                    |
| — at 400 V rated value                                            | 80 A               |
| — at 500 V rated value                                            | 80 A               |
| — at 690 V rated value                                            | 58 A               |
| • at AC-4 at 400 V rated value                                    | 55 A               |
| • at AC-5a up to 690 V rated value                                | 79.2 A             |
| • at AC-5b up to 400 V rated value                                | 66.4 A             |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=20 rated value             | 70 A               |
| — up to 400 V for current peak value n=20 rated value             | 70 A               |
| — up to 500 V for current peak value n=20 rated value             | 70 A               |
| — up to 690 V for current peak value n=20 rated value             | 58 A               |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=30 rated value             | 46.7 A             |
| — up to 400 V for current peak value n=30 rated value             | 46.7 A             |
| — up to 500 V for current peak value n=30 rated value             | 46.7 A             |
| — up to 690 V for current peak value n=30 rated value             | 46.7 A             |
| minimum cross-section in main circuit at maximum AC-1 rated value | 35 mm <sup>2</sup> |
| operational current for approx. 200000 operating cycles at AC-4   |                    |
| • at 400 V rated value                                            | 30 A               |
| • at 690 V rated value                                            | 24 A               |
| operational current                                               |                    |
| • at 1 current path at DC-1                                       |                    |
| — at 24 V rated value                                             | 55 A               |
| — at 60 V rated value                                             | 23 A               |
| — at 110 V rated value                                            | 4.5 A              |
| — at 220 V rated value                                            | 1 A                |
| — at 440 V rated value                                            | 0.4 A              |
| — at 600 V rated value                                            | 0.25 A             |
| • with 2 current paths in series at DC-1                          |                    |
| — at 24 V rated value                                             | 55 A               |
| — at 60 V rated value                                             | 45 A               |
| — at 110 V rated value                                            | 45 A               |
| — at 220 V rated value                                            | 5 A                |
| — at 440 V rated value                                            | 1 A                |
| — at 600 V rated value                                            | 0.8 A              |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• with 3 current paths in series at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 45 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 2.9 A                                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1.4 A                                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 35 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 6 A                                                         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1 A                                                         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.1 A                                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.06 A                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 45 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 25 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 5 A                                                         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.27 A                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.16 A                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 55 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 25 A                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.6 A                                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.35 A                                                      |
| <b>operating power</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                             |
| • at AC-2 at 400 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 37 kW                                                       |
| • at AC-3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                             |
| — at 230 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 22 kW                                                       |
| — at 400 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 37 kW                                                       |
| — at 500 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 37 kW                                                       |
| — at 690 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 45 kW                                                       |
| • at AC-3e                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                             |
| — at 230 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 22 kW                                                       |
| — at 400 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 37 kW                                                       |
| — at 500 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 37 kW                                                       |
| — at 690 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 45 kW                                                       |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                             |
| • at 400 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 15.8 kW                                                     |
| • at 690 V rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 21.8 kW                                                     |
| <b>operating apparent power at AC-6a</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                             |
| • up to 230 V for current peak value n=20 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 27.8 kVA                                                    |
| • up to 400 V for current peak value n=20 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 48.4 kVA                                                    |
| • up to 500 V for current peak value n=20 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 60.6 kVA                                                    |
| • up to 690 V for current peak value n=20 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 69.3 kVA                                                    |
| <b>operating apparent power at AC-6a</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                             |
| • up to 230 V for current peak value n=30 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 18.6 kVA                                                    |
| • up to 400 V for current peak value n=30 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 32.3 kVA                                                    |
| • up to 500 V for current peak value n=30 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 40.4 kVA                                                    |
| • up to 690 V for current peak value n=30 rated value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 55.8 kVA                                                    |
| <b>short-time withstand current in cold operating state up to 40 °C</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                             |
| • limited to 1 s switching at zero current maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1 298 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 5 s switching at zero current maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 898 A; Use minimum cross-section acc. to AC-1 rated value   |
| • limited to 10 s switching at zero current maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 640 A; Use minimum cross-section acc. to AC-1 rated value   |
| • limited to 30 s switching at zero current maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 414 A; Use minimum cross-section acc. to AC-1 rated value   |
| • limited to 60 s switching at zero current maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 333 A; Use minimum cross-section acc. to AC-1 rated value   |
| <b>no-load switching frequency</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                             |

|                                                                                       |                                                 |
|---------------------------------------------------------------------------------------|-------------------------------------------------|
| • at DC                                                                               | 1 500 1/h                                       |
| <b>operating frequency</b>                                                            |                                                 |
| • at AC-1 maximum                                                                     | 700 1/h                                         |
| • at AC-2 maximum                                                                     | 350 1/h                                         |
| • at AC-3 maximum                                                                     | 500 1/h                                         |
| • at AC-3e maximum                                                                    | 500 1/h                                         |
| • at AC-4 maximum                                                                     | 150 1/h                                         |
| <b>Control circuit/ Control</b>                                                       |                                                 |
| <b>type of voltage of the control supply voltage</b>                                  | DC                                              |
| <b>control supply voltage at DC</b>                                                   |                                                 |
| • rated value                                                                         | 24 V                                            |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |                                                 |
| • initial value                                                                       | 0.8                                             |
| • full-scale value                                                                    | 1.2                                             |
| <b>design of the surge suppressor</b>                                                 | with varistor                                   |
| <b>inrush current peak</b>                                                            | 2.6 A                                           |
| <b>duration of inrush current peak</b>                                                | 50 µs                                           |
| <b>locked-rotor current mean value</b>                                                | 0.9 A                                           |
| <b>locked-rotor current peak</b>                                                      | 2.1 A                                           |
| <b>duration of locked-rotor current</b>                                               | 230 ms                                          |
| <b>holding current mean value</b>                                                     | 40 mA                                           |
| <b>closing power of magnet coil at DC</b>                                             | 21.5 W                                          |
| <b>holding power of magnet coil at DC</b>                                             | 1 W                                             |
| <b>closing delay</b>                                                                  |                                                 |
| • at DC                                                                               | 35 ... 80 ms                                    |
| <b>opening delay</b>                                                                  |                                                 |
| • at DC                                                                               | 30 ... 55 ms                                    |
| <b>arcing time</b>                                                                    | 10 ... 20 ms                                    |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>                                                              |                                                 |
| number of NC contacts for auxiliary contacts instantaneous contact                    | 1                                               |
| number of NO contacts for auxiliary contacts instantaneous contact                    | 1                                               |
| operational current at AC-12 maximum                                                  | 10 A                                            |
| <b>operational current at AC-15</b>                                                   |                                                 |
| • at 230 V rated value                                                                | 10 A                                            |
| • at 400 V rated value                                                                | 3 A                                             |
| • at 500 V rated value                                                                | 2 A                                             |
| • at 690 V rated value                                                                | 1 A                                             |
| <b>operational current at DC-12</b>                                                   |                                                 |
| • at 24 V rated value                                                                 | 10 A                                            |
| • at 48 V rated value                                                                 | 6 A                                             |
| • at 60 V rated value                                                                 | 6 A                                             |
| • at 110 V rated value                                                                | 3 A                                             |
| • at 125 V rated value                                                                | 2 A                                             |
| • at 220 V rated value                                                                | 1 A                                             |
| • at 600 V rated value                                                                | 0.15 A                                          |
| <b>operational current at DC-13</b>                                                   |                                                 |
| • at 24 V rated value                                                                 | 10 A                                            |
| • at 48 V rated value                                                                 | 2 A                                             |
| • at 60 V rated value                                                                 | 2 A                                             |
| • at 110 V rated value                                                                | 1 A                                             |
| • at 125 V rated value                                                                | 0.9 A                                           |
| • at 220 V rated value                                                                | 0.3 A                                           |
| • at 600 V rated value                                                                | 0.1 A                                           |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>                                                                 |                                                 |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |                                                 |
| • at 480 V rated value                                                                | 65 A                                            |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 62 A                                                                                                                                                                              |
| <b>yielded mechanical performance [hp]</b> <ul style="list-style-type: none"> <li>• for single-phase AC motor <ul style="list-style-type: none"> <li>— at 110/120 V rated value</li> <li>— at 230 V rated value</li> </ul> </li> <li>• for 3-phase AC motor <ul style="list-style-type: none"> <li>— at 200/208 V rated value</li> <li>— at 220/230 V rated value</li> <li>— at 460/480 V rated value</li> <li>— at 575/600 V rated value</li> </ul> </li> </ul>                                                                                      | 5 hp<br>15 hp<br><br>20 hp<br>25 hp<br>50 hp<br>60 hp                                                                                                                             |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | A600 / P600                                                                                                                                                                       |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                   |
| <b>design of the fuse link</b> <ul style="list-style-type: none"> <li>• for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of assignment 2 required</li> </ul> </li> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>                                                                                                                                                                                                  | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)<br>gG: 160A (690V,100kA), aM: 80A (690V,100kA), BS88: 125A (415V,80kA)<br>gG: 10 A (500 V, 1 kA) |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                   |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                                              |
| <b>fastening method</b> <ul style="list-style-type: none"> <li>• side-by-side mounting</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715<br>Yes                                                                                                   |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 114 mm                                                                                                                                                                            |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 55 mm                                                                                                                                                                             |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 130 mm                                                                                                                                                                            |
| <b>required spacing</b> <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                                                     |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                   |
| <b>type of electrical connection</b> <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                               | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals                                                                                      |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                                      | 2x (1 ... 35 mm²), 1x (1 ... 50 mm²)<br>2x (1 ... 25 mm²), 1x (1 ... 35 mm²)<br>2x (18 ... 2), 1x (18 ... 1)                                                                      |
| <b>connectable conductor cross-section for main contacts</b> <ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                             | 1 ... 35 mm²                                                                                                                                                                      |
| <b>connectable conductor cross-section for auxiliary contacts</b> <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                           | 0.5 ... 2.5 mm²<br>0.5 ... 2.5 mm²                                                                                                                                                |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                 | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)                                                                                                                                       |

|                                                                |                                             |
|----------------------------------------------------------------|---------------------------------------------|
| — finely stranded with core end processing                     | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) |
| • for AWG cables for auxiliary contacts                        | 2x (20 ... 16), 2x (18 ... 14)              |
| <b>AWG number as coded connectable conductor cross section</b> |                                             |
| • for main contacts                                            | 18 ... 1                                    |
| • for auxiliary contacts                                       | 20 ... 14                                   |

| Safety related data                                                            |                                                  |
|--------------------------------------------------------------------------------|--------------------------------------------------|
| <b>proportion of dangerous failures</b>                                        |                                                  |
| • with low demand rate according to SN 31920                                   | 40 %                                             |
| • with high demand rate according to SN 31920                                  | 73 %                                             |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>           | 100 FIT                                          |
| <b>B10 value with high demand rate according to SN 31920</b>                   | 1 000 000                                        |
| suitability for use safety-related switching OFF                               | Yes                                              |
| <b>T1 value for proof test interval or service life according to IEC 61508</b> | 20 a                                             |
| <b>protection class IP on the front according to IEC 60529</b>                 | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>                    | finger-safe, for vertical contact from the front |

| Approvals Certificates   |
|--------------------------|
| General Product Approval |



[Confirmation](#)



[KC](#)



| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

| Marine / Shipping |
|-------------------|
|-------------------|



| Marine / Shipping | other | Railway | Environment |
|-------------------|-------|---------|-------------|
|-------------------|-------|---------|-------------|



[Confirmation](#)

[Vibration and Shock](#)

[Environmental Confirmations](#)

| Further information |
|---------------------|
|---------------------|

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2038-1KB40>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2038-1KB40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-1KB40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2038-1KB40&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2038-1KB40&lang=en)


Characteristic: Tripping characteristics,  $I^2t$ , Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-1KB40/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2038-1KB40&objecttype=14&gridview=view1>





last modified:

11/7/2023