



Panduit PLT2I-C96A Antimicrobial Met-Det Cable Tie

PLT2I-C96A

Panduit PLT2I-C96A Metal Detectable Cable Ties are designed to help the food and beverage industries meet product manufacturing safety standards. Featuring metal impregnated material, these cable ties are identifiable by metal detection equipment. Additionally, their antimicrobial properties help to reduce the growth of bacteria, fungus and mold. Intermediate cross section, 8.0" (203mm) length. Made of Metal Detectable Nylon 6.6, blue in color, and come in packages of 100.

Specifications

Product Type	Cable Tie
Color	Blue
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	8
Overall Length (mm)	203
Body Width (In.)	0.135
Body Width (mm)	3.4
Body Thickness (In.)	0.047
Body Thickness (mm)	1.2
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.13
Minimum Bundle Diameter (mm)	3.3
Minimum Loop Tensile Strength (N)	133
Minimum Loop Tensile Strength (lb)	30
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, ST2S, STH3
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	61305682370
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3208