



Straight Female Stud Fitting Type FI-GA-...-R • Series L / S



Female Whitworth Parallel Pipe Thread (BSPP)

Ordering Codes

FI-GA-10*L*R*-W3*-MS

* Straight Female Stud Fitting	FI-GA
* Outside Tube Diameter D1 (in mm)	-10
* Series	Light Series Heavy Series
* Thread Type	Female Whitworth Parallel Pipe Thread (BSPP)
	R
If required, please indicate special sizes, e.g. R3/8!	
* Material Code	Steel, zinc/nickel-plated
	-W3
Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Fitting body only
	—
	Fitting body supplied with cutting ring and union nut
	-MS
	Fitting body supplied with soft-sealing cutting ring and union nut
	-MSV

Connecting Parts

	Cutting Ring Type FI-DS	Page 26
	Soft-Sealing Cutting Ring Type FI-WDDS	Page 27
	Support Sleeve Type FI-VH	Page 28
	STAUFF Form Ring Type FI-AR	Page 30
	Union Nut Type FI-M	Page 31
	37° Flared Tube Fitting Set Type FI-AB	Page 35

Series	Tube OD (mm/in) D1	PN (bar/psi)	Dimensions (mm/in) Thread T	D2	L	L1 ¹	L2	L3	S1	S2	Weight (kg/lbs) ca. per 100 ²	Ordering Codes ³
L	6	315	G 1/8	4	26	34	19	12	14	14	3,26	FI-GA-06LR-W3
	.24	4568	G 1/8	.16	1.02	1.34	.75	.47	.55	.55	7.16	FI-GA-06LR1/4-W3
	6	315	G 1/4	4	31	39	24	18	19	14	3,78	FI-GA-08LR-W3
	.24	4568	G 1/4	.16	1.22	1.54	.94	.71	.75	.55	8.32	FI-GA-08LR3/8-W3
	8	315	G 3/8	6	31	39	24	17	19	17	3,91	FI-GA-08LR1/2-W3
	.31	4568	G 3/8	.24	1.22	1.54	.94	.67	.75	.67	8.61	FI-GA-10LR-W3
	8	315	G 1/2	6	31	39	24	16	24	17	2,28	FI-GA-10LR3/8-W3
	.31	4568	G 1/2	.24	1.22	1.54	.94	.63	.94	.67	5.02	FI-GA-10LR1/2-W3
	10	315	G 3/4	8	32	40	25	17	19	19	3,95	FI-GA-12LR-W3
	.39	4568	G 3/4	.31	1.26	1.57	.98	.67	.75	.75	8.69	FI-GA-12LR3/8-W3
	10	315	G 1	8	32	40	25	16	24	19	4,94	FI-GA-12LR1/2-W3
	.39	4568	G 1	.31	1.26	1.57	.98	.63	.94	.75	10.86	FI-GA-12LR1/4-W3
	10	315	G 1 1/4	8	37	45	30	20	27	19	8,36	FI-GA-12LR3/8-W3
	.39	4568	G 1 1/4	.31	1.46	1.77	1.18	.79	1.06	.75	18.39	FI-GA-15LR-W3
	12	315	G 1 1/2	8	33	41	26	17	19	22	4,44	FI-GA-15LR3/8-W3
	.47	4568	G 1 1/2	.31	1.3	1.61	1.02	.67	.75	.87	9.76	FI-GA-18LR-W3
	12	315	G 1 3/4	10	33	41	26	17	24	22	6,43	FI-GA-18LR3/8-W3
	.47	4568	G 1 3/4	.39	1.3	1.61	1.02	.67	.94	.87	14.14	FI-GA-22LR-W3
	12	315	G 2	10	37	45	30	20	27	22	8,38	FI-GA-22LR3/8-W3
	.47	4568	G 2	.39	1.46	1.77	1.18	.79	1.06	.87	18.44	FI-GA-28LR-W3
	15	315	G 2 1/2	12	38	46	31	20	27	27	8,84	FI-GA-28LR3/8-W3
	.59	4568	G 2 1/2	.47	1.50	1.81	1.22	.79	1.06	1.06	19.46	FI-GA-35LR-W3
	18	315	G 2 3/4	15	34	43	26,5	20	27	32	9,61	FI-GA-35LR3/8-W3
	.71	4568	G 2 3/4	.59	1.34	1.69	1.04	.79	1.06	1.26	21.15	FI-GA-42LR-W3
	18	315	G 3	15	38	47	30,5	20	27	32	9,15	FI-GA-42LR3/8-W3
	.71	4568	G 3	.59	1.50	1.85	1.20	.79	1.06	1.26	20.14	FI-GA-42LR1/2-W3
	22	160	G 3 1/4	19	43	52	35,5	22	36	36	17,87	FI-GA-22LR-W3
	.87	2320	G 3 1/4	.75	1.69	2.05	1.40	.87	1.42	1.42	39.31	FI-GA-28LR-W3
	28	160	G 1	24	45,5	54,5	38	24,5	41	41	21,80	FI-GA-35LR-W3
	1.1	2320	G 1	.94	1.79	2.15	1.50	.96	1.61	1.61	47.96	FI-GA-42LR-W3
	35	160	G 1 1/4	30	51,5	62,5	41	26,5	55	50	47,49	FI-GA-42LR3/8-W3
	1.38	2320	G 1 1/4	1.18	2.03	2.46	1.61	1.04	2.17	1.97	104.47	FI-GA-42LR1/2-W3
	42	160	G 1 1/2	36	53,5	65,5	42,5	28,5	60	60	53,90	FI-GA-38SR-W3
	1.65	2320	G 1 1/2	1.42	2.11	2.58	1.67	1.12	2.36	2.36	118.58	
S	6	630	G 1/4	4	33	41	26	17	19	17	4,33	FI-GA-06SR-W3
	.24	9135	G 1/4	.16	1.3	1.61	1.02	.67	.75	.67	9.52	FI-GA-08SR-W3
	8	630	G 3/8	5	33	41	26	17	19	19	4,53	FI-GA-10SR-W3
	.31	9135	G 3/8	.2	1.30	1.61	1.02	.67	.75	.75	9.96	FI-GA-12SR-W3
	10	630	G 1	7	34	43	26,5	17	24	22	6,99	FI-GA-12SR1/2-W3
	.39	9135	G 1	.28	1.34	1.69	1.04	.67	.94	.87	15.37	FI-GA-14SR-W3
	12	630	G 1 1/2	8	34	43	26,5	17	24	24	7,08	FI-GA-16SR-W3
	.47	9135	G 1 1/2	.31	1.34	1.69	1.04	.67	.94	.94	15.57	FI-GA-20SR-W3
	12	630	G 1 3/4	8	38	47	30,5	20	27	24	9,23	FI-GA-25SR-W3
	.47	9135	G 1 3/4	.31	1.50	1.85	1.20	.79	1.06	.94	20.31	FI-GA-30SR-W3
	14	630	G 2	10	40	50	32	20	27	27	9,64	FI-GA-38SR-W3
	.55	9135	G 2	.39	1.57	1.97	1.26	.79	1.06	1.06	21.20	
	16	630	G 2 1/2	12	40	50	31,5	20	27	30	9,70	FI-GA-20SR-W3
	.63	9135	G 2 1/2	.47	1.57	1.97	1.24	.79	1.06	1.18	21.33	FI-GA-25SR-W3
	20	400	G 3	16	45	56	34,5	22	36	36	19,50	FI-GA-30SR-W3
	.79	5800	G 3	.63	1.77	2.20	1.36	.87	1.42	1.42	42.90	FI-GA-38SR-W3
	25	400	G 1 1/4	20	49,5	61,5	37,5	24,5	41	46	25,14	
	.98	5800	G 1 1/4	.79	1.95	2.42	1.48	.96	1.61	1.81	55.30	
	30	400	G 1 3/4	25	55,5	68,5	42	26,5	55	50	51,30	
	1.18	5800	G 1 3/4	.98	2.19	2.70	1.65	1.04	2.17	1.97	112.86	
	38	315	G 2 1/2	32	59,5	74,5	43,5	28,5	60	60	62,80	
	1.50	4568	G 2 1/2	1.26	2.34	2.93	1.71	1.12	2.36	2.36	138.16	

¹ Approximate dimension in assembled condition.

² Weight excluding cutting ring and union nut.

³ Standard scope of delivery: Fitting body only.
