

**Reflex Servitec 35/T, 90°C,
vacuum spray deaeration/make-up unit
Article-No.:8832100**



Reflex Servitec

Vacuum spray tube degassing for system and makeup water degassing in closed heating and cooling circuits, configured as a fully automatic multi-function unit with ?auto-start? function and automatic hydraulic compensation of the degassing process and monitoring of the makeup function. Suitable for the media water and water/glycol mixtures up to a mixing ratio of 50/50%.

Functional unit comprising a hydraulic part and a Control Touch operating unit. Both are ergonomically combined in an easy-to-maintain modular floor-standing framework system made of EV 1 anodized aluminium precision sections with CE marking.

Degassing takes place within the hydraulic part using a stainless steel diaphragm pump in conjunction with a vertically arranged stainless steel vacuum spray tube. This is equipped with a vacuum spray nozzle, dipstick-tube degassing unit and pressure/level monitoring.

The Control Touch operating unit with TFT colour display inclusive of communications electronics is integrated in a panel-type rugged plastic housing and mounted directly on the control unit with a horizontal alignment. An optional separate and vertical wall mounting plate at maximum three metres distance from the power electronics is possible.

Communication electronics comprising:

- 4,3" resistive colour touchscreen for programming, operating documentation and monitoring as well as provision of help texts for all functions
- Two RS485 serial interfaces as data and/or communication interfaces
- Serial TTL-interface with two connection terminals for connection of 2 IO-boards
- Potential-free output for forwarding of the collective message
- Two electrically isolated analogue outputs e.g. for system pressure
- Input for the evaluation of contact water meters
- Slot for a compact bus module, one SD card, e.g. for data read-out, software updates, etc.
- Input for makeup functional request via external signal

The power electronics are installed in a dedicated plastic control cabinet which is mounted directly below the operating unit. Power supply is via a main switch. Featuring in detail:

- Main switch on housing exterior
- Pump control
- Cable management for external connections
- Mounting slot for optional modules

Control unit completely piped and wired ready for connection according to VDE regulations. System connections by means of integrated shut-off valves.

Control Touch is a fully automatic and freely programmable microprocessor control with touchscreen operation, real-time clock, differentiating error and parameter memory, combined graphical and clear-text display of system pressure, tank level and all relevant operating and fault messages with functional diagram. Signalling of the active operating mode, collective fault message, low water level and functioning of pump and makeup valve.

Vacuum spray degassing of the content, filling and make-up water in self-optimising operation with cycles for continuous, interval and make-up degassing. Controlled make-up via reliable two-way motorised ball valve. Actuation takes place via an integrated system pressure interpretation unit or an external 230 V signal (e.g. a pressure maintenance station) with automatic interruption and fault messaging upon exceeding of the running time and/or the number of cycles. Alternatively, make-up can be performed from an open system separator vessel. Evaluation option provided by a contact water meter including optional possible capacity monitoring of ion exchangers in the make-up pipe. Documentation and control of the entire system in respect of the above mentioned parameters.

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident.-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen

**Reflex Servitec 35/T, 90°C,
vacuum spray deaeration/make-up unit
Article-No.:8832100**



Merkmale

Type: 35
adm. excess oper. press.: 8 bar
adm. operating temp.: 90 °C
adm. ambient temp.: >0..35 °C
sound level: < 55 dB(A)
power supply: 230V/50Hz
electr. power cons.: 0,70 kW
electr. nominal curr.: 5,00 A
depth x width x height (mm): 486/553/965
empty weight: 30,0 kg
connections pressure-side: G 1"
flow-off side: G 1/2"
make-up: G 1/2"
elimin. degree dissolved gases: up to 90%
part. vol.flow netw. up to: 0,550 m³/h
make-up volume flow up to: 0,350 m³/h
water content: I
heat generator SV: bar
advance press. exp. vessel: bar
final press. press.maint.: bar
min. flow press. make-up: bar



09.09.2020 18:02

Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen