

Codan 2801 Welding & Gas Hose



Codan 2801 - ISO 3821:2010

Lightweight, flexible, smooth, red hose for acetylene, to EN559. For use with industrial autogenic welding equipment, usually together with blue oxygen hose.

Also ideal for natural gas and air.

Please contact Codan for further information.

Type nr. 2801

Application: Acetylene

Standard Length: 50 metres

Working Temperature: -30°C to 80°C

Inside: EPDM

Colour: Black

Reinforcement: Ester

Outside: EPDM

Colour: Red

Standards: ISO 3821:2010

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	13,3	20	60	63	146	2801006000
8,0	14,6	20	60	80	172	2801008000
10,0	17,0	20	60	100	203	2801010000
12,5	19,4	20	60	125	257	2801013000
20,0	27,2	20	60	200	399	2801019000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

02/06/2015