



code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
												
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1364251	38	1-1/2	52	2,05	16	240	48	720	1,24	0,83	120	400
1298089	51	2	67	2,64	16	240	48	720	1,78	1,20	120	400
1394126	63,5	2-1/2	78,5	3,09	16	240	48	720	1,99	1,34	120	400
1393553	76	3	91	3,59	16	240	48	720	2,34	1,58	120	400
1388487	102	4	119	4,69	16	240	48	720	3,45	2,32	120	400
1282310	152	6	169,5	6,68	16	240	48	720	4,94	3,32	120	400
1282301	203	8	224	8,83	16	240	48	720	8,11	5,45	60	200



IT

Tubo per mandata carburanti ed olio

Applicazione: tubo cord utilizzato per passaggio di prodotti petroliferi con contenuto aromatico fino al 50%.

Temperatura: da -20°C a +70°C.

Costruzione

Sottostrato: nero, liscio in gomma PVC/NBR.

Rinforzo: tessuti sintetici ad alta resistenza e trecce rame antistatiche.

Copertura: nera, liscia (ad impressione tela) in gomma sintetica resistente agli agenti atmosferici ed all'olio.

Marcatura: transfer ad elica di colore giallo: "Oil (Logo famiglia)...".

EN

Fuel and oil delivery hose

Application: softwall hose used for the delivery of petroleum products with aromatic content up to 50%.

Temperature: from -20°C(-4°F) to +70°C(+158°F).

Construction

Tube: black, smooth PVC/NBR rubber.

Reinforcement: high strength synthetic cord plus antistatic copper wire.

Cover: black, smooth (wrapped finish) synthetic rubber, weathering and oil resistant.

Branding: yellow transfer tape: "Oil (Family logo)...".