


NPT - Male with 60°-Cone



| Pressure | Thread |             | Approx. Dimensions |      |      |      |    | Order-Code    |
|----------|--------|-------------|--------------------|------|------|------|----|---------------|
|          | PN     | G = NPT     | G1 = NPT           | L    | L1   | D    | SW |               |
| 630      |        | 1/8"-27     | 1/8"-27            | 27,0 | 10,0 | 5,0  | 12 | 1282810-02-02 |
| 630      |        | 1/4"-18     | 1/4"-18            | 36,5 | 15,0 | 7,0  | 14 | 1282810-04-04 |
| 630      |        | 3/8"-18     | 3/8"-18            | 36,5 | 15,3 | 9,0  | 19 | 1282810-06-06 |
| 630      |        | 1/2"-14     | 1/2"-14            | 48,4 | 20,0 | 13,5 | 22 | 1282810-08-08 |
| 630      |        | 3/4"-14     | 3/4"-14            | 50,0 | 20,0 | 18,0 | 27 | 1282810-12-12 |
| 400      |        | 1"-11,5     | 1"-11,5            | 59,0 | 25,0 | 21,0 | 36 | 1282810-16-16 |
| 400      |        | 1 1/4"-11,5 | 1 1/4"-11,5        | 63,0 | 25,5 | 31,5 | 46 | 1282810-20-20 |
| 400      |        | 1 1/2"-11,5 | 1 1/2"-11,5        | 65,0 | 26,0 | 36,0 | 50 | 1282810-24-24 |
| 315      |        | 2"-11,5     | 2"-11,5            | 68,0 | 26,0 | 46,0 | 65 | 1282810-32-32 |