

Spiral Wrapping Band


Description:

Spiral wrapping with excellent binding strength for Harness Breakout:

Wire Harnessing, cabling and bundling work is simplified with the use of Brady's series of Spiral Wrap tubing. The tubing wraps tightly to the wire and cable being bundled, yet is flexible and is simple to apply. All types maintain Flexibility even when bent around sharp edges. Breakouts or tap-off connections may be made through the openings of the wrap. Brady Spiral Wrap is constructed from several semi-rigid tubing materials and then cut on a continual spiral.. Flexible construction encables bands to follow wire ways easily. Durable and reusable with retained spiral strength. Easy install: fix ends of band with Brady cable ties and spiral wire bundles in clockwise direction to complete works. A economical way of cable binding. Easily applied to electric harness, cable and wire bundles.

This cost-effective material is extremely abrasion resistant and is unaffected by most solvents. Clear Polyethylene is Ideal for general indoor applications. Black Polyethylene is Ideal for general indoor & outdoor applications. Black PE is Ultraviolet resistant.

TECHNICAL CHARACTERISTICS



DIMENSIONS

EAN number	Description	Colour	D1	D	W	Wrapping range mm
5703666 701278	Spiralflex Ø4,5	Natural	4,5	3,2	7,0	4 ~ 25
5703666 700851	Spiralflex Ø6,0	Natural	6,2	4,1	7,0	4 ~ 25
5703666 700875	Spiralflex Ø8,0	Natural	8,0	6,0	10,8	6 ~ 30
5703666 700899	Spiralflex Ø10,0	Natural	10,0	7,5	11,4	7,5 ~ 30
5703666 700912	Spiralflex Ø12,0	Natural	12,0	9,0	13,9	9 ~ 32
5703666 700936	Spiralflex Ø19,0	Natural	19,0	15,0	18,2	15 ~ 50
5703666 700868	Spiralflex Ø6,0	Black	6,2	4,1	7,0	4 ~ 25
5703666 700882	Spiralflex Ø8,0	Black	8,0	6,0	10,8	6 ~ 30
5703666 700905	Spiralflex Ø10,0	Black	10,0	7,5	11,4	7,5 ~ 30
5703666 700929	Spiralflex Ø12,0	Black	12,0	9,0	13,9	9 ~ 32
5703666 700943	Spiralflex Ø19,0	Black	19,0	15,0	18,2	15 ~ 50

Standard colour:

Natural and Black

Matrial:

Polyethylene.

Operating temperature:

-20°C to +80°C.

Specifications:



Applications:

Wire Harness Breakouts

Cable Bundling

Handling:

No special handling requirements.

Notes:

This information and data is believed to be accurate and reliable. Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of this date, Brady makes no representations as to the completeness or accuracy thereof. We place at your disposal the technical information necessary for the correct use of our products. As conditions and methods of use are beyond our control, that the person receiving the same will make their own determination as to the suitability for their purpose.

We reserve the right to modify characteristics with the aim of improving the product and adapting it to the requirements of the market.