


BSP - Male with 60°-Cone  
BSP - Taper - Male  
Other sizes on request!



| Pressure |         | Thread    |   | Approx. Dimensions |    |   |    |  | Order-Code |
|----------|---------|-----------|---|--------------------|----|---|----|--|------------|
| PN       | G = BSP | G1 = BSPT | L | L1                 | L2 | D | SW |  |            |

**Series A**

|     |           |           |      |    |    |      |    |               |
|-----|-----------|-----------|------|----|----|------|----|---------------|
| 400 | 1/8"-28   | 1/8"-28   | 23,0 | 8  | 8  | 4,0  | 14 | 1050710-02-02 |
| 400 | 1/4"-19   | 1/4"-19   | 30,0 | 10 | 12 | 6,0  | 19 | 1050710-04-04 |
| 400 | 3/8"-19   | 3/8"-19   | 32,5 | 12 | 12 | 9,0  | 22 | 1050710-06-06 |
| 400 | 1/2"-14   | 1/2"-14   | 37,0 | 14 | 14 | 12,5 | 27 | 1050710-08-08 |
| 400 | 3/4"-14   | 3/4"-14   | 47,0 | 16 | 19 | 17,5 | 32 | 1050710-12-12 |
| 400 | 1"-11     | 1"-11     | 49,0 | 18 | 18 | 22,0 | 41 | 1050710-16-16 |
| 200 | 1 1/4"-11 | 1 1/4"-11 | 54,5 | 20 | 20 | 29,0 | 50 | 1050710-20-20 |
| 200 | 1 1/2"-11 | 1 1/2"-11 | 58,5 | 22 | 22 | 37,0 | 55 | 1050710-24-24 |
| 100 | 2"-11     | 2"-11     | 66,0 | 25 | 26 | 45,0 | 70 | 1050710-32-32 |

**Series B**

|     |         |         |      |    |    |      |    |               |
|-----|---------|---------|------|----|----|------|----|---------------|
| 400 | 1/4"-19 | 1/8"-28 | 26,0 | 10 | 8  | 4,0  | 19 | 1050710-04-02 |
| 400 | 1/4"-19 | 3/8"-19 | 32,0 | 10 | 12 | 7,0  | 19 | 1050710-04-06 |
| 400 | 1/4"-19 | 1/2"-14 | 34,0 | 10 | 14 | 6,0  | 22 | 1050710-04-08 |
| 400 | 3/8"-19 | 1/4"-19 | 33,0 | 12 | 12 | 7,0  | 22 | 1050710-06-04 |
| 400 | 3/8"-19 | 1/2"-14 | 42,0 | 12 | 19 | 9,0  | 22 | 1050710-06-08 |
| 400 | 1/2"-14 | 3/8"-19 | 37,0 | 14 | 12 | 9,0  | 27 | 1050710-08-06 |
| 400 | 1/2"-14 | 3/4"-14 | 45,0 | 14 | 19 | 12,5 | 27 | 1050710-08-12 |
| 400 | 3/4"-14 | 1/2"-14 | 45,0 | 16 | 19 | 12,5 | 32 | 1050710-12-08 |
| 400 | 3/4"-14 | 1"-14   | 45,0 | 16 | 18 | 17,5 | 36 | 1050710-12-16 |