

FRIGA-BOHN - -

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com

FRIGA-BOHN®Item : **Item 16**Typ : **Cubic**

Date 01/05/2025

Version : 4.22

**NOVA 3155 C (Multi Refrigerant)****Total capacity : 2,03 kW****DT1 (Dew) / DTM (Mean) : 5,2 / 8 K**

DeltaT1 = Difference between air inlet temperature and Dew temperature (Evaporator outlet before superheat).

Operating conditions

Refrigerant :	R454C	A2L
Room temperature :	-20 °C	
Unit number :	1	
Pressure :	-1 bar / 25 bar	

Aeraulic characteristics (per unit)

Nb. and diameter of fans :	1 x 315 (AC fan)
Air flow-rate :	1810 m ³ /h
Pressure :	0 Pa
Air throw :	18 m
Lp (at 4m) :	33 dB(A)

Coil characteristics (per unit)

Surface :	8.9 m ²
Volume :	2,1 dm ³ (915 g)
Fin spacing :	6 mm
Inlet / Outlet :	5/8"-5/8" (D)

Electrical characteristics (per unit)

Rotation speed :	1350 tr/min
Maximum input power :	1 x 90 W
Maximum operating current :	1 x 0,4 A
Motor coupling :	-
Voltage/ Nb Phases / Frequency :	230V / 1 / 50-60Hz

Dimensional characteristics (per unit)

Dimensions (L/D/H) :	772/530/428 mm
Empty net weight :	22 kg
Packaging (L/D/H) :	850 / 560 / 510 mm
Packed unit weight :	27 kg
Standard packaging :	Cardboard box

Standard defrost characteristics

Defrost power :	1720 W
Defrost current :	7.48 A
Voltage/ Nb Phases / Frequency :	230V / 1 / 50Hz
Number of elements :	3 + 1



Fluid group 1 according to ESP directive 2014/68/UE. A risk assessment must be carried out in accordance with EN 378:2017 before implementation.

(1) The average acoustic pressure level in dB(A) measured at 4 m, at fan height, in direct line of sight on a reflective surface, are given as an example. Only the acoustic pressure spectrum and Lw value, are contractually binding and may be used to evalu

All prices are retail prices 2025. Our proposals, quotes and order acceptances are subject to our general terms of sale.

FRIGA-BOHN - -

42, Rue Roger SALENGRO BP 205

69 741 GENAS - FRANCE

Tel. : +33(0)472 471 444 - Fax : +33(0)472 471 399

Email : customer.serv@lennoxemea.com



Item : **Item 16**

Typ : **Cubic**

Date 01/05/2025

Version : 4.22

Model : NOVA 3155 C

(Drawings are only indicative)

