


Series 020 (DN 5 bis DN 50)
 Body, Connecting Parts, Ball and Stem Stainless Steel,
 V4a (AISI 316)
 Each PH ball valve is subject to an inspection for
 resistance, sealing
 and special characteristics.
 Inspection control certificates 3.1 B or 3.1 C per DIN EN
 10204 can be
 supplied on request against invoice.
 Other materials as 254Smo or Hastelloy, etc. on request.



Ball Sealing: POM
 Stem Sealing: NBR

Corrosive Media
 -20°C to 100°C

The indicated working pressure PB is only valid for the
 standard version 4423.
 Max. allowed pressure (PB) see at the data from the
 compression couplings.

Measurements subject to alteration.



General Information

Weight kg	Pressure		Thread		Approx. Dimensions mm										Order-Code	
	DN	PB	D	B	H	H1	H2	H4	i	L	L1	M	SW	SW"		
0,35	5	500	G 1/8"	35	43,5	32	8,0	13,0	9	69	36	M 5	22	9	RKH-G 1/8"-4423	
0,35	6	500	G 1/4"	35	43,5	32	8,0	13,0	12	69	36	M 5	22	9	RKH-G 1/4"-4423	
0,5	10	500	G 3/8"	42	49,5	38	8,0	16,5	12	73	43	M 5	27	9	RKH-G 3/8"-4423	
0,65	13	500	G 1/2"	45	51,5	40	8,0	17,5	14	85	48	M 5	30	9	RKH-G 1/2"-4423	
0,75	16	400	G 5/8"	50	62,0	46	12,0	19,0	14	84	48	M 6	32	12	RKH-G 5/8"-4423	
1,5	20	400	G 3/4"	60	73,0	57	12,0	24,5	17	96	62	M 6	41	14	RKH-G 3/4"-4423	
1,8	24	400	G 1"	65	79,0	63	12,0	28,0	19	113	66	M 6	46	14	RKH-G 1"-4423	
3,8	32	350	G 1 1/4"	90	104,0	84	13,5	38,0	20	110	81	M 8	60	17	RKH-G 1 1/4"-4423	
6,1	38	350	G 1 1/2"	100	112,0	93	13,5	42,5	22	120	86	M 8	70	17	RKH-G 1 1/2"-4423	
9,1	48	350	G 2"	120	131,0	111	13,5	50,0	28	140	101	M 8	85	17	RKH-G 2"-4423	