

RTR1362 - Dobbeltklæbende vævtape - perm /peel

Description	Dobbeltklæbende vævtape med akrylbaseret klæber med differentieret klæbekraft
Product properties	Tapen er fremstillet af et speciel lærred med permanent akrylklæber på den lukkede side (11 N/25 mm) og en aftagbar akrylklæber på den åbne side (10 N/25 mm), som ikke efterlader limrester. Klæberne er resistente overfor opløsningsmidler.
Applications	Anbefales til midlertidig montering af tæpper til messer og udstillinger. Også velegnet til gulve med PVC overflade og tæpper med bagside af PVC.
Processing guidelines	Den aftagbare klæber vender ind mod kerne (=åbne side)
Storage and ageing	Holdbarhed min. 2 år ved 21°C, 50% luftfugtighed og ikke i direkte sollys.
Applying tips	Overfladen, hvor tapen monteres, skal være ren, tør og fri for fedt og olie. Emnerne skal, så vidt muligt have samme temperatur.

TECHNICAL DATA

Carrier	Cloth	
Adhesive	Acrylic modified	
Colour	White	
Liner	Paper silicone coated white	
Plasticizer resistant	Yes	
Ageing resistant	Yes	
Thickness Total	0,34 mm	13,4 Mils
Adhesion on stainless steel	9 N/25mm	2,06 Lbs/inch
Adhesion on stainless steel, closed side	11 N/25mm	2,51 Lbs/inch
Static shear 23°C	2 kg/625mm ²	4,55 Lb/inch ²
Static shear 23°C, closed side	0,5 kg/625mm ²	1,14 Lb/inch ²
Service temperature	Between -40 and 100 °C	Between -40 and 212 °F
Application temperature	Minimum 15 °C	Minimum 59 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes (UK) Ltd
Unit 8, Tring Industrial Estate
Icknield Way, Tring, Hertfordshire
tel +44 (0)14 42 82 17 00
fax +44 (0)14 42 82 17 22
www.stokvistapes.co.uk
info@stokvistapes.co.uk