


Rundhovedet – Alu/Stål - Lukket



MFX 1201

Ø d	l	Nitte evne	Beskrivelse	Ø d _k	k	Ø d _m	p	Træk (N)	Snit (N)
mm	mm	mm		mm	mm	mm	mm		
3,2	6,5	0,5-2,0	1201 3206	6,0 +/-0,24	≤1,4	~1,70	≥27	1250	1070
(+/-0,08)	8,0	2,0-3,5	1201 3208						
	9,5	3,5-5,0	1201 3209						
Ø3,3	10,7	5,0-6,5	1201 3210						
	12,7	6,5-8,0	1201 3212						
4,0	8,0	0,5-3,5	1201 4008	8,0 +/-0,29	≤1,7	~2,18	≥27	2240	1700
(+/-0,08)	9,5	3,5-4,5	1201 4009						
	11,0	4,5-6,5	1201 4011						
Ø4,1	12,7	6,5-8,0	1201 4012						
	15,0	8,0-10,5	1201 4015						
4,8	8,0	1,0-3,0	1201 4808	9,5 +/-0,29	≤2,0	~2,63	≥27	3100	2200
(+/-0,08)	9,5	3,0-4,5	1201 4809						
	11,0	4,5-6,0	1201 4811						
Ø4,9	12,5	6,0-7,5	1201 4812						
	14,0	7,5-9,0	1201 4814						
	16,0	9,0-11,0	1201 4816						
	18,0	11,0-13,0	1201 4818						
	21,0	13,0-16,0	1201 4821						
	25,0	16,0-20,0	1201 4825						
6,4	12,5	1,5-6,0	1201 6412	12,7 +/-0,35	≤2,5	~3,70	≥31	4900	3950
(+/-0,11)	16,0	6,0-8,0	1201 6416						
									
Ø6,5									