

Codan 2808 Welding & Gas Hose



Codan 2808 - EN 559: 2003

Flexible twin hose for propane/butane and oxygen.
Dividing groove allows easy separation.
Specially designed for industrial cutting and welding tasks.
Normally installed using hose clamps or swaged on fittings.
Please contact Codan for further information.

Type nr. 2808
Application: Oxygen / LPG (Propane / Butane)
Standard Length: 50 metres
Working Temperature: -25°C to 80°C
Inside: NBR
Colour: Black
Reinforcement: PVA
Outside: SBR
Colour: Blue/Orange
Standards: EN 559: 2003
Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
5,0	11,0	20	60	55	300	2808505000
6,3	12,0	20	60	60	350	2808606000
6,3	16,0	20	80	80	400	2808608000
8,0	15,0	20	60	90	500	2808808000
10,0	17,0	20	60	120	760	2808909000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Fax +45 56 64 65 48
Mail: info@codan.com www.codan.com

22/03/2019