

Cable trays, perforated

PTCSU-0018



Type	Dimensions A/B/C mm	Weight kg/100 m	EAN code	Ref. No.
Cable tray W3				
Perforated cable tray for indoor or outdoor industrial applications. System height 40 mm. Provided with holes Ø 5.8 mm at the tray end to be used for fixation of joints. Oval holes along the lateral sides of the tray can be used for mounting of accessories. Material: Steel, hot-dip galvanized.				
W3/40-50	40/50/3000	110	7321677354009	735400
W3/40-70	40/70/3000	120	7321677354016	735401
W3/40-100	40/100/3000	156	7321677354023	735402
W3/40-150	40/150/3000	170	7321677354030	735403
W3/40-200	40/200/3000	220	7321677354047	735404
W3/40-300	40/300/3000	350	7321677354054	735405
W3/40-400	40/400/3000	453	7321677354061	735406
W3/40-500	40/500/3000	620	7321677354078	735407
W3/40-600	40/600/3000	723	7321677354085	735408

ODAT35982.9is



Installation tray W4				
Perforated installation tray for indoor or outdoor industrial applications. To be used when leading cables down from a cable ladder to machine cabinets, etc. Provided with holes Ø 3.5 mm in the bottom segment of the tray for the clamping of cables with plate screws. Material: Steel, hot-dip galvanized.				
W4-50	15/50/1960	57	7321677366132	736613
	15/50/3000	57	7321677359776	735977
W4-75	15/75/1960	76	7321677366149	736614
	15/75/3000	76	7321677359783	735978
W4-100	15/100/1960	93	7321677366156	736615
	15/100/3000	93	7321677359790	735979
W4-150	15/150/1960	125	7321677366163	736616
	15/150/3000	125	7321677359806	735980
W4-200	15/200/1960	195	7321677366170	736617
	15/200/3000	195	7321677359813	735981
W4-250	15/250/1960	228	7321677366187	736618
	15/250/3000	228	7321677359820	735982
W4-300	15/300/1960	238	7321677366194	736619
W4-400	15/400/1960	313	7321677366200	736620

Lighting trunking

PTCSU-0019



Lighting trunking W70-50, -70, -100				
Cable tray with bottom perforation for indoor applications in dry environments. System height 40 mm, length 3000 mm. Oval holes 9x5.8 mm on the lateral sides of the tray end can be used for fixation of joints. The oval hole pattern at the base of the tray can be used for mounting of lighting fixtures. On every 500 mm an oval hole is placed to easily guide fast connectors into the tray. Material: Steel, hot-dip galvanized.				
W70-50	40/50/3000	271	3606480756115	CSU795218
W70-70	40/70/3000	293	3606480464812	CSU794528
W70-100	40/100/3000	346	3606480464829	CSU794529



Covers

P140357



Type	Dimensions A/B/C mm	Weight kg/100 pcs	EAN code	Ref. No.
Cover W5				
Cover to be used to protect the cables inside the cable tray against damages, dust, liquids, UV-influence, etc. Material: Sheet steel, hot-dip galvanized.				
W5-70	10/71/2000	160	7321677322626	732262
W5-100	10/101/2000	210	7321677322633	732263
W5-150	10/151/2000	290	7321677322640	732264
W5-200	10/201/2000	370	7321677322657	732265
W5-300	10/301/2000	540	3606480535734	732266
W5-400	10/401/2000	710	7321677322671	732267
W5-500	10/501/2000	880	7321677322688	732268
W5-600	10/601/2000	1050	7321677322695	732269

P146808



Cover clamp W62				
Cover clamp to be used for the fixing of covers on cable trays W3 as well as on lighting trunking W70. Material: Stainless steel 304.				
W62	-/15/10.5	0.8	7321677301867	730186