

ASPIR PVC/AS

Code 4522



I. Diam. Toll. EN ISO 1307 [mm]	E. Diam. [mm]	Pitch [mm]	Weight +/-5% [g/m]	Vacuum at 20°C [bar]	Coil length max. [m]	
10		5,5				
12		6,0				
13		6,0				
14		6,0				
16		6,5				
18		7,0				
19		7,0				
20		7,0				
22		7,0				
25		7,5				
28		8,0				
30		8,0				
32		8,0				
35		8,5				
38		8,5				
40		8,5				
42		8,5				
45		8,5				
51	61	9,5	900	0,55	50	
55		10,0				
60		10,0				
63	75	10,25	1150	0,5	50	
65		10,5				
70		10,5				
76	88	11,0	1450	0,4	50	
80		11,0				
90		13,0				
102	116	13,0	2020	0,3	30	
110		13,0				
120		13,0				
127		15,0				
130		15,0				
140		15,5				
152		15,5				
160		15,5				
180		15,5				
203		20,0				
254		24,0				
305		28,0				

Description:

PVC Ductinghose

Extremely flexible elastic grade Vacuum Hose designed to achieve optimum flexibility with a tight bend radius.

Temperature range:

-15 °C / +60 °C

Construction:

Soft orange PVC, rigid PVC spiral with PU-protected static wire.
Inside smooth, outside corrugated.

Bending radius:

3 times inside diameter

