


## VKA Blanking plug for cones

EO 24° DKO swivel



X1) O-ring OR

| Series          | D1<br> | L1   | Weight<br>g/1 piece | Order code*  | PN (bar) <sup>1)</sup> |     |     |
|-----------------|--------|------|---------------------|--------------|------------------------|-----|-----|
|                 |        |      |                     |              | CF                     | 71  | MS  |
| L <sup>3)</sup> | 06     | 18.5 | 6                   | <b>VKA06</b> | 500                    | 315 | 200 |
|                 | 08     | 18.5 | 9                   | <b>VKA08</b> | 500                    | 315 | 200 |
|                 | 10     | 20.0 | 15                  | <b>VKA10</b> | 500                    | 315 | 200 |
|                 | 12     | 20.5 | 21                  | <b>VKA12</b> | 400                    | 315 | 200 |
|                 | 15     | 20.5 | 32                  | <b>VKA15</b> | 400                    | 315 | 200 |
|                 | 18     | 22.5 | 49                  | <b>VKA18</b> | 400                    | 315 | 200 |
|                 | 22     | 25.0 | 80                  | <b>VKA22</b> | 250                    | 160 | 100 |
|                 | 28     | 25.5 | 131                 | <b>VKA28</b> | 250                    | 160 | 100 |
|                 | 35     | 30.0 | 240                 | <b>VKA35</b> | 250                    | 160 | 100 |
|                 | 42     | 30.0 | 343                 | <b>VKA42</b> | 250                    | 160 | 100 |
| S <sup>4)</sup> | 06     | 18.5 | 6                   | <b>VKA06</b> | 800                    | 630 | 400 |
|                 | 08     | 18.5 | 9                   | <b>VKA08</b> | 800                    | 630 | 400 |
|                 | 10     | 20.0 | 15                  | <b>VKA10</b> | 800                    | 630 | 400 |
|                 | 12     | 20.5 | 21                  | <b>VKA12</b> | 630                    | 630 | 400 |
|                 | 14     | 22.5 | 30                  | <b>VKA14</b> | 630                    | 630 | 400 |
|                 | 16     | 23.5 | 40                  | <b>VKA16</b> | 630                    | 400 | 250 |
|                 | 20     | 28.5 | 78                  | <b>VKA20</b> | 420                    | 400 | 250 |
|                 | 25     | 29.0 | 120                 | <b>VKA25</b> | 420                    | 400 | 250 |
|                 | 30     | 30.5 | 180                 | <b>VKA30</b> | 420                    | 400 | 250 |
|                 | 38     | 33.0 | 309                 | <b>VKA38</b> | 420                    | 315 | 200 |

<sup>1)</sup> Pressure shown = item deliverable

<sup>3)</sup> L = light series; <sup>4)</sup> S = heavy series

$$\frac{PN \text{ (bar)}}{10} = PN \text{ (MPa)}$$

Information on ordering alternative sealing materials see page 17.

\*Please add the **suffixes** below according to the material/surface required.

| Order code suffixes             |                             |         |                                                         |
|---------------------------------|-----------------------------|---------|---------------------------------------------------------|
| Material                        | Suffix surface and material | Example | Standard sealing material (no additional suffix needed) |
| Steel, zinc plated, Cr(VI)-free | CF                          | VKA16CF | NBR                                                     |
| Stainless Steel                 | 71                          | VKA1671 | VIT                                                     |
| Brass                           | MS                          | VKA16MS | NBR                                                     |