



Circuit breaker size S3 for motor protection, CLASS 10 A-release 65...84 A N-release 1170 A screw terminal Increased switching capacity 100 kA

|                                                                                     |                      |
|-------------------------------------------------------------------------------------|----------------------|
| product brand name                                                                  | SIRIUS               |
| product designation                                                                 | Circuit breaker      |
| design of the product                                                               | For motor protection |
| product type designation                                                            | 3RV2                 |
| <b>General technical data</b>                                                       |                      |
| size of the circuit-breaker                                                         | S3                   |
| size of contactor can be combined company-specific                                  | S3                   |
| product extension auxiliary switch                                                  | Yes                  |
| power loss [W] for rated value of the current                                       |                      |
| • at AC in hot operating state                                                      | 34 W                 |
| • at AC in hot operating state per pole                                             | 11.3 W               |
| insulation voltage with degree of pollution 3 at AC rated value                     | 1 000 V              |
| surge voltage resistance rated value                                                | 8 kV                 |
| shock resistance according to IEC 60068-2-27                                        | 25g / 11 ms Sinus    |
| mechanical service life (operating cycles)                                          |                      |
| • of the main contacts typical                                                      | 25 000               |
| • of auxiliary contacts typical                                                     | 25 000               |
| electrical endurance (operating cycles) typical                                     | 25 000               |
| type of protection according to ATEX directive 2014/34/EU                           | Ex II (2) GD         |
| certificate of suitability according to ATEX directive 2014/34/EU                   | DMT 02 ATEX F 001    |
| reference code according to IEC 81346-2                                             | Q                    |
| Substance Prohibitance (Date)                                                       | 03/01/2017           |
| SVHC substance name                                                                 | Blei - 7439-92-1     |
| <b>Ambient conditions</b>                                                           |                      |
| installation altitude at height above sea level maximum                             | 2 000 m              |
| ambient temperature                                                                 |                      |
| • during operation                                                                  | -20 ... +60 °C       |
| • during storage                                                                    | -50 ... +80 °C       |
| • during transport                                                                  | -50 ... +80 °C       |
| relative humidity during operation                                                  | 10 ... 95 %          |
| <b>Main circuit</b>                                                                 |                      |
| number of poles for main current circuit                                            | 3                    |
| adjustable current response value current of the current-dependent overload release | 65 ... 84 A          |
| operating voltage                                                                   |                      |
| • rated value                                                                       | 20 ... 690 V         |
| • at AC-3 rated value maximum                                                       | 690 V                |
| • at AC-3e rated value maximum                                                      | 690 V                |
| operating frequency rated value                                                     | 50 ... 60 Hz         |
| operational current rated value                                                     | 84 A                 |

|                                                                      |                                                                          |
|----------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>operational current</b>                                           |                                                                          |
| • at AC-3 at 400 V rated value                                       | 84 A                                                                     |
| • at AC-3e at 400 V rated value                                      | 84 A                                                                     |
| <b>operating power</b>                                               |                                                                          |
| • at AC-3                                                            |                                                                          |
| — at 230 V rated value                                               | 22 kW                                                                    |
| — at 400 V rated value                                               | 45 kW                                                                    |
| — at 500 V rated value                                               | 55 kW                                                                    |
| — at 690 V rated value                                               | 75 kW                                                                    |
| • at AC-3e                                                           |                                                                          |
| — at 230 V rated value                                               | 22 kW                                                                    |
| — at 400 V rated value                                               | 45 kW                                                                    |
| — at 500 V rated value                                               | 55 kW                                                                    |
| — at 690 V rated value                                               | 75 kW                                                                    |
| <b>operating frequency</b>                                           |                                                                          |
| • at AC-3 maximum                                                    | 15 1/h                                                                   |
| • at AC-3e maximum                                                   | 15 1/h                                                                   |
| <b>Protective and monitoring functions</b>                           |                                                                          |
| <b>product function</b>                                              |                                                                          |
| • ground fault detection                                             | No                                                                       |
| • phase failure detection                                            | Yes                                                                      |
| <b>trip class</b>                                                    | CLASS 10                                                                 |
| <b>design of the overload release</b>                                | thermal                                                                  |
| <b>maximum short-circuit current breaking capacity (Icu)</b>         |                                                                          |
| • at AC at 240 V rated value                                         | 100 kA                                                                   |
| • at AC at 400 V rated value                                         | 100 kA                                                                   |
| • at AC at 500 V rated value                                         | 10 kA                                                                    |
| • at AC at 690 V rated value                                         | 6 kA                                                                     |
| <b>operating short-circuit current breaking capacity (Ics) at AC</b> |                                                                          |
| • at 240 V rated value                                               | 100 kA                                                                   |
| • at 400 V rated value                                               | 50 kA                                                                    |
| • at 500 V rated value                                               | 5 kA                                                                     |
| • at 690 V rated value                                               | 3 kA                                                                     |
| response value current of instantaneous short-circuit trip unit      | 1 170 A                                                                  |
| <b>UL/CSA ratings</b>                                                |                                                                          |
| <b>full-load current (FLA) for 3-phase AC motor</b>                  |                                                                          |
| • at 480 V rated value                                               | 84 A                                                                     |
| • at 600 V rated value                                               | 84 A                                                                     |
| <b>yielded mechanical performance [hp]</b>                           |                                                                          |
| • for single-phase AC motor                                          |                                                                          |
| — at 110/120 V rated value                                           | 7.5 hp                                                                   |
| — at 230 V rated value                                               | 15 hp                                                                    |
| • for 3-phase AC motor                                               |                                                                          |
| — at 200/208 V rated value                                           | 25 hp                                                                    |
| — at 220/230 V rated value                                           | 30 hp                                                                    |
| — at 460/480 V rated value                                           | 60 hp                                                                    |
| — at 575/600 V rated value                                           | 75 hp                                                                    |
| <b>Short-circuit protection</b>                                      |                                                                          |
| <b>product function short circuit protection</b>                     | Yes                                                                      |
| <b>design of the short-circuit trip</b>                              | magnetic                                                                 |
| <b>Installation/ mounting/ dimensions</b>                            |                                                                          |
| <b>mounting position</b>                                             | any                                                                      |
| <b>fastening method</b>                                              | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715 |
| <b>height</b>                                                        | 165 mm                                                                   |
| <b>width</b>                                                         | 70 mm                                                                    |
| <b>depth</b>                                                         | 176 mm                                                                   |
| <b>required spacing</b>                                              |                                                                          |
| • with side-by-side mounting at the side                             | 0 mm                                                                     |
| • for grounded parts at 400 V                                        |                                                                          |
| — downwards                                                          | 70 mm                                                                    |

|                               |        |
|-------------------------------|--------|
| — upwards                     | 70 mm  |
| — at the side                 | 10 mm  |
| • for live parts at 400 V     |        |
| — downwards                   | 70 mm  |
| — upwards                     | 70 mm  |
| — at the side                 | 10 mm  |
| • for grounded parts at 500 V |        |
| — downwards                   | 110 mm |
| — upwards                     | 110 mm |
| — at the side                 | 10 mm  |
| • for live parts at 500 V     |        |
| — downwards                   | 110 mm |
| — upwards                     | 110 mm |
| — at the side                 | 10 mm  |
| • for grounded parts at 690 V |        |
| — downwards                   | 150 mm |
| — upwards                     | 150 mm |
| — at the side                 | 30 mm  |
| • for live parts at 690 V     |        |
| — downwards                   | 150 mm |
| — upwards                     | 150 mm |
| — at the side                 | 30 mm  |

#### Connections/ Terminals

|                                                                      |                                                                    |
|----------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>type of electrical connection</b>                                 |                                                                    |
| • for main current circuit                                           | screw-type terminals                                               |
| <b>arrangement of electrical connectors for main current circuit</b> | Top and bottom                                                     |
| <b>type of connectable conductor cross-sections</b>                  |                                                                    |
| • for main contacts                                                  |                                                                    |
| — solid                                                              | 2x (2.5 ... 16 mm <sup>2</sup> )                                   |
| — solid or stranded                                                  | 2x (2.5 ... 50 mm <sup>2</sup> ), 1x (10 ... 70 mm <sup>2</sup> )  |
| — finely stranded with core end processing                           | 2x (2.5 ... 35 mm <sup>2</sup> ), 1x (2.5 ... 50 mm <sup>2</sup> ) |
| — finely stranded without core end processing                        | 2x (10 ... 35 mm <sup>2</sup> ), 1x (10 ... 50 mm <sup>2</sup> )   |
| <b>tightening torque</b>                                             |                                                                    |
| • for main contacts for ring cable lug                               | 4.5 ... 6 N·m                                                      |
| <b>outer diameter of the usable ring cable lug maximum</b>           | 19 mm                                                              |
| <b>tightening torque</b>                                             |                                                                    |
| • for main contacts with screw-type terminals                        | 4.5 ... 6 N·m                                                      |

#### Safety related data

|                                                                                |                                                  |
|--------------------------------------------------------------------------------|--------------------------------------------------|
| <b>proportion of dangerous failures</b>                                        |                                                  |
| • with low demand rate according to SN 31920                                   | 50 %                                             |
| • with high demand rate according to SN 31920                                  | 50 %                                             |
| <b>B10 value with high demand rate according to SN 31920</b>                   | 5 000                                            |
| <b>T1 value for proof test interval or service life according to IEC 61508</b> | 10 a                                             |
| <b>protection class IP on the front according to IEC 60529</b>                 | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>                    | finger-safe, for vertical contact from the front |
| display version for switching status                                           | Handle                                           |

#### Approvals Certificates

|                          |                                 |
|--------------------------|---------------------------------|
| General Product Approval | For use in hazard-ous locations |
|--------------------------|---------------------------------|

[Confirmation](#)



[KC](#)



|                                 |                           |                   |                   |
|---------------------------------|---------------------------|-------------------|-------------------|
| For use in hazard-ous locations | Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------------|---------------------------|-------------------|-------------------|



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



Marine / Shipping

other



[Household and similar appliances](#)

other

Railway

Environment

[Confirmation](#)



[Vibration and Shock](#)

[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2042-4RA10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2042-4RA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2042-4RA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2042-4RA10&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2042-4RA10&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2042-4RA10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV2042-4RA10&objecttype=14&gridview=view1>



