

Cable protection hoses/Ventilation hoses

Cavocord



Cable protecting hose

Used to protect hoses, lines, cables, especially for portable welding equipment.

Temperature range	: -30°C / +80°C
Tube	: Syntetic rubber, textile impregnated,
Cover	: SBR, black, fabric finish

ø Inner mm	Wall mm	ø Outer mm	Length mtr	Art.-No.
20	1,5	23	40	3290 020000
22	1,5	25	40	3290 022000
25	1,5	28	40	3290 025000
28	1,5	31	40	3290 028000
30	1,5	33	40	3290 030000
32	1,5	35	40	3290 032000
35	1,5	38	40	3290 035000
40	1,5	43	40	3290 040000
45	1,5	48	40	3290 045000
51	1,5	54	40	3290 050000

Airflex®



Thermoplastic suctionhose

for air, gasses, smoke, dust and chemical gasses. Also suitable for cable protection. Kinkproof and extremely flexible. Not suitable for sparkles or welding residues.

Temperature range	: -15°C / +60°C
Structure	: PVC, grey, with embedded spiral of rigid PVC inside smooth, outside corrugated
Bending radius	: 1 X inside diameter

Marking:  AIRFLEX® - SIZE

ø Inner mm	ø Outer mm	Vacuum bar	kg / mtr	Length mtr	Art.-No.
20	25	0,6	0,140	30	4500 020000
25	31	0,55	0,200	50	4500 025000
32	38	0,45	0,240	50	4500 032000
38	45	0,45	0,320	50	4500 038000
40	47	0,45	0,360	50	4500 040000
45	52	0,4	0,410	50	4500 045000
51	58	0,4	0,480	50	4500 050000
60	68	0,4	0,600	50	4500 060000
63	72	0,4	0,660	50	4500 063000
70	79	0,4	0,760	50	4500 070000
76	85	0,4	0,780	50	4500 075000
80	90	0,4	0,900	50	4500 080000
90	101	0,4	1,080	50	4500 090000
102	112	0,4	1,160	50	4500 100000
110	121	0,35	1,400	30	4500 110000
120	130	0,35	1,450	30	4500 120000
127	138	0,35	1,500	20	4500 125000
152	164	0,3	1,900	20	4500 150000
160	172	0,3	2,100	20	4500 160000
180	193	0,25	2,350	20	4500 180000
203	219	0,2	2,900	20	4500 200000
254	270	0,2	3,700	10	4500 250000
305	324	0,1	4,800	10	4500 300000

Cuttet length possible.