



code	inside diameter		weight nominal		bending radius		vacuum	length max	
									
	mm	inch	kg/m	lbs/ft	mm	inch	bar	m	ft
1296140	102	4	3,38	2,27	410	16,2	0,9	60	200
1291980	127	5	4,17	2,80	510	20,1	0,9	60	200
1278266	152	6	4,91	3,30	610	24,0	0,9	60	200
1282620	203	8	8,89	5,97	810	31,9	0,9	60	200



IT

Tubo per aspirazione materiali abrasivi

Applicazione: tubo per aspirazione prodotti abrasivi. Utilizzato come linea di connessione su macchine pulitrici.

Temperatura: da -30°C a +70°C.

Costruzione

Sottostrato: in gomma NR/SBR, nera, liscia.

Rinforzo: tessuti sintetici ad alta resistenza, spirale d'acciaio e trecce rame antistatiche incorporate.

Copertura: in gomma EPDM, nera, ondulata (ad impressione tela), resistente agli agenti atmosferici e all'ozono.

Marcatura: transfer IVG di colore giallo.

Disponibili a richiesta: 1. Fornito con manicotti lunghi 50 mm.

EN

Material handling suction hose

Application: used as "connection line" on vacuum cleaner machines for suction of abrasion materials.

Temperature: from -30°C (-22°F) to +70°C (+158°F).

Construction

Tube: NR/SBR rubber, black, smooth.

Reinforcement: high strength synthetic cord, steel helix wire and antistatic copper wires protruding.

Cover: EPDM rubber, black, corrugated (wrapped finish), weathering and ozone resistant.

Branding: IVG yellow transfer tape.

Also available upon request: 1. Supplied with soft ends 50 mm long.