



Cover Plate Type DP



STAUFF Group 1



STAUFF Group 1A to 8

Ordering Codes

Cover Plate


***DP-*1-*W3**

* Cover Plate	DP
* STAUFF Group	1
* Material code	Carbon Steel, zinc/nickel-plated W3
	Stainless Steel V2A W4
	1.4301 / 1.4305 (AISI 304 / 303)
	Stainless Steel V4A W5
	1.4401 / 1.4571 (AISI 316 / 316 Ti)
	Aluminium EN AW-6060 W85

Group STAUFF	DIN	Dimensions (mm/m)		B	S	ØD	Ordering Codes (Standard Options)
L1	L2						
1	0	28	9,5	30	3	7	DP-1-W3
		1.10	.37	1.18	.12	.28	
1A	1	34	20	30	3	7	DP-1A-W3
		1.34	.79	1.18	.12	.28	
2	2	40,5	26	30	3	7	DP-2-W3
		1.59	1.02	1.18	.12	.28	
3	3	48	33	30	3	7	DP-3-W3
		1.89	1.30	1.18	.12	.28	
4	4	57	40	30	3	7	DP-4-W3
		2.24	1.57	1.18	.12	.28	
5	5	70	52	30	3	7	DP-5-W3
		2.76	2.05	1.18	.12	.28	
6	6	86	66	30	3	7	DP-6-W3
		3.39	2.60	1.18	.12	.28	
7	7	118	94	30	5	7	DP-7-W3
		4.65	3.70	1.18	.20	.28	
8	8	144	120	30	5	7	DP-8-W3
		5.67	4.72	1.18	.20	.28	

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Hexagon Head Bolt (for Use with Cover Plate DP) Type AS



Hexagon Head Bolt AS (according to DIN 931 / 933 or ANSI / ASME B18.2.1.)
Dimensions applicable only when used with Cover Plate DP

Ordering Codes

Hexagon Head Bolt *AS-*M6x30-*W3

* Type of bolt	Hexagon Head Bolt (according to DIN 931 / 933 or ANSI / ASME B18.2.1.)	AS
* Thread type and size acc. to dimension table		M6x30
* Material code	Carbon Steel, zinc/nickel-plated	W3
	Stainless Steel V2A	
	1.4301 / 1.4305 (AISI 304 / 303)	W4
	Stainless Steel V4A	
	1.4401 / 1.4571 (AISI 316 / 316 Ti)	W5

Group STAUFF	DIN	Dimensions (mm/m) Thread G x L	Ordering Codes (Standard Options)
1	0	M6 x 30	AS-M6x30-W3
		1/4-20 UNC x 1-1/4	AS-1/4-20UNCx1-1/4-W3
1A	1	M6 x 30	AS-M6x30-W3
		1/4-20 UNC x 1-1/4	AS-1/4-20UNCx1-1/4-W3
2	2	M6 x 35	AS-M6x35-W3
		1/4-20 UNC x 1-3/8	AS-1/4-20UNCx1-3/8-W3
3	3	M6 x 40	AS-M6x40-W3
		1/4-20 UNC x 1-1/2	AS-1/4-20UNCx1-1/2-W3
4	4	M6 x 45	AS-M6x45-W3
		1/4-20 UNC x 1-7/8	AS-1/4-20UNCx1-7/8-W3
5	5	M6 x 60	AS-M6x60-W3
		1/4-20 UNC x 2-3/8	AS-1/4-20UNCx2-3/8-W3
6	6	M6 x 70	AS-M6x70-W3
		1/4-20 UNC x 2-3/4	AS-1/4-20UNCx2-3/4-W3
7	7	M6 x 100	AS-M6x100-W3
		1/4-20 UNC x 4	AS-1/4-20UNCx4-W3
8	8	M6 x 125	AS-M6x125-W3
		1/4-20 UNC x 4-7/8	AS-1/4-20UNCx4-7/8-W3

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table.
Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

