

CONTENT

AIR & WATER

AIR CONDITION

BRAKE

BREATHING

BUNKER

CHEMICAL

COOLANT

FOOD

FUEL

GAS

HYDRAULIC

MATERIAL HANDLING

OIL

OIL COOLING

POWERSTEERING

PVC

STEAM

WELDING & GAS

INDEX

Codan 3006 Oil Hose



Codan 3006 -

Black, flexible, anti-static pressure hose for oil. A classic oil hose for all-round industrial use, e.g. diesel, paraffin, grease and other oil-based media. Extremely hard-wearing, weather and ozone-resistant, self-extinguishing outer CR rubber coating. Normally installed using hose clamps, but clamp or screw fittings can also be used. Note! Care must be taken to avoid damaging the yarn insert. Please contact Codan for further information.

Type nr. 3006

Application: Oil / Grease / Universal

Standard Length: 50 metres

Working Temperature: -40°C to 100°C

Inside: NBR

Colour: Black

Reinforcement: Ester

Outside: CR

Colour: Black

Standards:

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	14,3	20	80	20	191	3006006000
7,9	15,9	20	80	25	221	3006008000
9,5	17,5	20	60	30	250	3006010000
12,7	21,5	20	60	50	350	3006013000
15,9	24,7	20	60	70	417	3006016000
19,1	29,5	15	50	90	588	3006019000
22,3	33,1	15	50	100	694	3006022000
25,4	36,2	15	50	120	770	3006025000
32,0	42,0	15	45	220	920	3006032000
38,0	48,0	15	45	250	1.060	3006038000
51,0	61,0	15	45	350	1.340	3006051000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanised Rubber Products).

The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.