


Adapters

FMK4 Male stud connector

BSPP 60° Cone end (ISO 8434-6) / Male NPTF* thread (SAE J476)

*Stainless Steel = NPT to prevent galling



Thread BSPP T4	Thread NPT/NPTF PTM	A mm	C mm	D mm	L mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)
1/8	1/8	10	14	4	24	17	2FMK4S	2FMK4SS	350
1/8	1/4	15	19	4	29	21	2-4FMK4S	2-4FMK4SS	350
1/4	1/8	10	19	5	29	24	4FMK4S	4FMK4SS	350
1/4	1/4	15	19	5	33	33	4-4FMK4S	4-4FMK4SS	350
1/4	3/8	15	19	5	34	41	4-6FMK4S	4-6FMK4SS	350
3/8	1/4	15	22	8	35	45	6FMK4S	6FMK4SS	350
3/8	3/8	15	2	8	35	50	6-6FMK4S	6-6FMK4SS	350
3/8	1/2	19	22	8	40	77	6-8FMK4S	6-8FMK4SS	350
1/2	3/8	15	27	11	39	48	8FMK4S	8FMK4SS	200
1/2	1/2	19	27	11	43	93	8-8FMK4S	8-8FMK4SS	200
1/2	3/4	19	27	11	44	95	8-12FMK4S	8-12FMK4SS	200
3/4	1/2	19	32	17	46	112	12-8FMK4S	12-8FMK4SS	200
3/4	3/4	19	32	17	46	124	12FMK4S	12FMK4SS	200
3/4	1	24	36	17	51	150	12-16FMK4S	12-16FMK4SS	200
1	3/4	19	41	22	50	188	16-12FMK4S	16-12FMK4SS	120
1	1	24	41	22	55	234	16FMK4S	16FMK4SS	120

Order codes shown are part of our current manufacturing programme.
Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.