

## DECLARATION OF PERFORMANCE

**DoP N° QP0030 - 2023**

**1. Unique identification code for product-type:**

CIM 11G - FULL BORE BALL VALVE FOR GAS - EN 331 - T12G SERIES - STEEL LEVER HANDLE

**2. Type, batch or serial number or any other element allowing identification of the construction product:**

|                       |                       |                       |                     |
|-----------------------|-----------------------|-----------------------|---------------------|
| 11G1/4 - QP00301008   | 11G3/8 - QP00301010   | 11G1/2 - QP00301015   | 11G3/4 - QP00301020 |
| 11G1 - QP00301025     | 11G1.1/4 - QP00301032 | 11G1.1/2 - QP00301040 | 11G2 - QP00301050   |
| 11G2.1/2 - QP00301070 | 11G3 - QP00301080     | 11G4 - QP00301100     |                     |

**3. Intended use or uses of the construction product**

Manually operated ball valves and closed bottom taper plug valves for gas installations for buildings.

**4. Manufacturer:**

Cav. Uff. Giacomo Cimberio S.p.A.  
Via Torchio, 57  
29017 San Maurizio d'Opaglio (NO)  
ITALY

**5. Where applicable, name and contact address of the authorised representative:**

Not applicable

**6. System of assessment and verification of constancy of performance referred to in the annex V:**

System 3

**7. In the case of a declaration of performance concerning a construction product falls within the scope of a harmonized standard:**

-

**8. Declared performances:**

| Characteristics                      | Performance     | Standard     |
|--------------------------------------|-----------------|--------------|
| <b>Dimensional tolerances</b>        | <b>Pass</b>     | <b>EN331</b> |
| <b>Temperature class</b>             | <b>-20÷60°C</b> | <b>EN331</b> |
| <b>Pressure class</b>                | <b>MOP5</b>     | <b>EN331</b> |
| <b>Leak-tightness</b>                | <b>Pass</b>     | <b>EN331</b> |
| <b>Rated flow rate</b>               | <b>Pass</b>     | <b>EN331</b> |
| <b>Operating torque</b>              | <b>Pass</b>     | <b>EN331</b> |
| <b>Torque and bending resistance</b> | <b>Pass</b>     | <b>EN331</b> |
| <b>Durability</b>                    | <b>Pass</b>     | <b>EN331</b> |
| <b>Angular seal</b>                  | <b>Pass</b>     | <b>EN331</b> |
| <b>Stop resistance</b>               | <b>Pass</b>     | <b>EN331</b> |
|                                      |                 |              |
|                                      |                 |              |
|                                      |                 |              |
|                                      |                 |              |

**9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8**

**10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4**

San Maurizio d'Opaglio, February 20, 2023

Cav. Uff. Giacomo Cimberio S.p.A



IMR 562637



FM 01820



EMS 551553



OHS 551552



ENMS 577357



n. 727