

Emergency stop rope pull switches with single anchor point ISO M20, Pg 13.5 and 1/2" NPT with integrated quick tensioner

Cable and end spring to be ordered separately (1)

Without pilot light

Cable length	Colors and materials	Reset	Supply voltage	Contact type	Cable anchor point	Reference	Weight kg	
≤ 30 m	Zamak red RAL 3000 body Stainless steel cover Chloroprene bellows	By flush pushbutton	—	 1 1	NC + NO slow break	RH side or LH side	XY2CH13150 (4)	0.865
		By booted pushbutton	—	 1 1			XY2CH13250 (3) (4)	0.865
		By mushroom head pushbutton	—	 1 1			XY2CH13350 (4)	0.900
		By key-operated pushbutton (key no. 421) (2)	—	 1 1			XY2CH13450 (3) (4)	0.910
	By flush pushbutton	—	 2 —	NC + NC slow break	RH side or LH side	XY2CH13170 (3) (4)	0.865	
	By booted pushbutton	—	 2 —			XY2CH13270 (3) (4)	0.865	
	By mushroom head pushbutton	—	 2 —			XY2CH13370 (3)	0.865	
	By key-operated pushbutton (key no. 421) (2)	—	 2 —			XY2CH13470 (3) (4)	0.910	
	By flush pushbutton	—	 2 1	2 NC + 1 NO slow break	RH side or LH side	XY2CH13190 (3) (4)	0.865	
	By booted pushbutton	—	 2 1			XY2CH13290 (3) (4)	0.865	
	By mushroom head pushbutton	—	 2 1			XY2CH13390 (3) (4)	0.865	

With orange pilot light (direct supply)

≤ 30 m	Red RAL 3000 body Stainless steel cover Chloroprene bellows	By booted pushbutton	24 V ~/—	1 1	NC + NO slow break	RH side or LH side	XY2CH13253 (3)	0.900
				2 —	NC + NC slow break		XY2CH13273	0.900
				2 1	2 NC + 1 NO slow break		XY2CH13293 (3)	0.950

Other versions

Versions with silicon bellows
Please contact our Customer Care Center.

(1) See separate parts on page 12.

(2) Ø 30 spring return key-operated mushroom head pushbutton.

(3) For ISO M20 tapped cable entry version, add H29 to the end of the selected reference.

For example: XY2CH13250 becomes XY2CH13250H29.

(4) For 1/2" NPT tapped cable entry version, add H7 to the end of the selected reference.

For example: XY2CH13190 becomes XY2CH13190H7.



XY2CH13250



XY2CH13450



XY2CH13170



XY2CH13253