

Codan 2806 Welding & Gas Hose



Codan 2806 - EN ISO 3821: 2019

Black, flexible hose for argon and nitrogen. Mainly for use in industrial argon-welding applications. Specially developed to prevent moisture from permeating into the hose from the outside. A very strong, non-porous weld is thus achieved. Please contact Codan for further information.

Type nr. 2806

Application: Argon / nitrogen

Standard Length: 50 metres

Working Temperature: -25°C to 80°C

Inside: EPDM

Colour: Black

Reinforcement: Polyester

Outside: SBR

Colour: Black

Standards: EN ISO 3821: 2019

Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,0	11,0	20	60	35	115	2806004000
5,0	11,0	20	60	50	119	2806005000
6,3	13,3	20	60	63	158	2806006000
8,0	15,0	20	60	80	175	2806008000
10,0	17,0	20	60	100	209	2806010000
12,5	22,5	20	60	125	300	2806013000
16,0	26,0	20	60	160	380	2806016000
19,1	29,0	20	60	200	450	2806019000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Mail: info@codan.com
www.codan.com

22/02/2022