

Danfoss GD Heavy Duty gas detection unit, ammonia (R717) electrochemical, 0–5000 ppm, LCD, wall-mount (148H6031)

Brand: Danfoss Part No: 148H6031 HS: 9027.10
Hazardous Area Equipment — Fixed Gas Detection

Description

Danfoss GD Heavy Duty fixed gas detection unit, code 148H6031, a factory-calibrated wall-mount detector for ammonia (R717) in refrigeration machinery rooms, cold stores and process plant. Electrochemical sensing element with a 0–5000 ppm measuring range and two-level alarm relays (pre-alarm 1000 ppm, main alarm 4500 ppm). On-board LCD display for local annunciation. Supplied as a complete unit with mounting kit, cable gland and a factory calibration certificate. Supply 16–28 V DC. Integrates with Danfoss AK-SM system managers and standard alarm panels. HS 9027.10. OEM P/N 148H6031.

Specifications

Type	Gas detection unit — GD Heavy Duty
Code number	148H6031
Detected gas	ammonia (R717)
Sensor technology	electrochemical
Measuring range	0–5000 ppm
Pre-alarm (low) set point	1000 ppm
Main alarm (high) set point	4500 ppm
Local annunciation	LCD display
Supply voltage	16–28 V DC
Operating temperature	-20 to +50 °C
Enclosure	wall-mount, includes mounting kit and cable gland
Supplied with	factory calibration certificate
Approvals	EU RoHS; China RoHS
EAN	5714279919738

Standards & Approvals

Standards: EU RoHS, China RoHS
Approvals: EU RoHS, China RoHS

