

Specifications



Eaton 001890

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar assemblies CI enclosure, for fitting busbar mounting fuse bases, 3-Pole, for 250 A rated operational current, can be used for CI44 

General specifications

PRODUCT NAME	Eaton xEnergy Safety Ci busbar assembly RS
CATALOG NUMBER	001890
MODEL CODE	SE-RS-I44
EAN	4015080018902
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	375 mm
PRODUCT WIDTH	375 mm
PRODUCT WEIGHT	1.096 kg
COMPLIANCES	RoHS conform

Additional information

FUNCTIONS

For fitting busbar mounting fuse bases
3 pole, for 250 A rated operational current
Prepared enclosure

SUITABLE FOR

Fitting busbar mounting fuse bases
3 pole, for 250 A rated operational current

USED WITH

CI44...
Prepared enclosures
xEnergy Safety Ci
Modular busbar system

Technical data - electrical

CURRENT RATING - MAX 250 A

Resources

BROCHURES

[eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf](#)

CATALOGUES

[eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf](#)

DRAWINGS

[eaton-insulated-boards-busbar-xenergy-safety-ci-busbar-support-3d-drawing.eps](#)

INSTALLATION INSTRUCTIONS

[eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Delivery programme

ACCESSORY/SPARE PART TYPE

Busbar assemblies

NUMBER OF POLES

Three-pole

TYPE

- Modular busbar system
- Prepared enclosures
- xEnergy Safety Ci

Technical data - mechanical

BUSBAR DISTANCE 50 mm

UNIT TYPE

Modular system